

Defender

POWER AND LIGHT

2017 | 2018
DEALER BROCHURE

Defender Power & Light was founded in Nottingham, UK in 1997. It is a leading brand in the global site lighting and power distribution industry and is represented in over 20 countries.

WHY CHOOSE DEFENDER?

It all comes down to performance and safety - our mission is to develop solutions that support user requirements and can be trusted to deliver the light and power users need to get the job done.

THE DEFENDER ETHOS

Durability and safety is at the heart of everything we do. Our products:

- > Need to withstand tough working conditions
- > Need to ensure safety for both the user and work sites
- > Are developed with NO compromise in quality

Defender Power & Light is owned by Birchwood Price Tools (BPT).



DEFENDER PRODUCT DEVELOPMENT

We understand how lighting and power are used in different situations. This helps us develop impact resistant products with improved functionality, that give clear advantages over traditional equivalents

> Our products are design engineered in the UK

> Our transformers are made in the UK

> We are pioneers in LED site lighting, having been the first into the UK market in 2009

> Partnerships with quality component manufacturers ensure excellent product performance



QUALITY ASSURANCE

> With two dedicated quality assurance offices in both Europe and Asia, our company BPT supports new product innovations with a thorough inspection policy

> BPT is proud to own a VDE* co-licence. This means our independently audited manufacturing plants work to stringent requirements to develop Defender power distribution products to a consistent premium quality

> BPT is registered as an ISO 9001:2008 organisation. The processes we have in place support our ambition to continually improve, understand and deliver customer and user needs

TESTED TO PERFORM

Our product and packaging are rigorously tested prior to launch to ensure optimum performance both in store and in use

Additionally:

- > Our products are certified using independent test houses
- > Our products are tested to recognised international standards, which include GS, CE, UL and SAA



*VDE - The Association for Electrical, Electronic and Information Technologies, see page 51 for more information



For more information or to become a distributor and enjoy the business opportunities delivered by our range of products and recognised brands, contact:

E - sales@birchwoodpricetools.com

Visit the Defender website: defenderpower.com

T - 0115 938 9000

View product videos on the Defender Power & Light YouTube channel

Order Online @birchwoodpricetools.com



LED6000S FLOODLIGHT RANGE

PAGE 6

This best selling LED floodlight is now stronger than ever. It's a smart, low power lightweight floodlight that packs a punch in terms of high light output.

Now with upgraded LEDs and a more productive LED driver and heat sink to drive greater efficiencies, it also features a tough tear resistant silicone sleeve to protect it from damage - drop tested to 2.5M.

The full range includes single head, twin head, tripod, scaffold and magnetic fixing options to suit user needs.

LED3000S FLOODLIGHT RANGE

PAGE 8

The LED3000S has been enhanced for 2017- driving greater efficiencies through the upgraded LEDs, driver and heat sink.

The full range includes single head, twin head, tripod, scaffold and magnetic fixing options to suit user needs.

LED ANTI-CORROSIVE RANGE

PAGE 19

This low power anti-corrosive range is made from an impact resistant, tough polycarbonate case to absorb knocks with ease.

The range includes 2ft and 5ft string task lights, fixed tripod and battery back options.

DF1200 LED FLOODLIGHT RANGE

PAGE 10

The DF1200 range is a low power and efficient alternative to Halogen floodlights. Featuring a universal bracket, the light head is available on a range of Defender tripods and fixings to suit user needs. Additionally rechargeable options are available.

The full range includes single head, twin head, tripod and scaffold and magnetic fixing options to suit user needs.

LED400 FLOOR LIGHT

PAGE 24

The LED400 floor light is a smart, lightweight portable light.

Ideal for small tasks. Rechargeable and corded options available.

LIGHTING RANGE

FLOODLIGHTS	6
TASK LIGHTS	16
FLOOR LIGHT	24
HAND LAMPS	26
FESTOON LIGHT CHAINS	28

POWER DISTRIBUTION RANGE

POWER & SITE TRANSFORMERS	30
POWER SPLITTERS	32
CABLE REELS	34
EXTENSION LEADS	36
FLY LEADS	38
CABLE DRUMS	38
PLUGS, SOCKETS & COUPLERS	38
RCD UNITS	40
GENERATORS	40
BULBS & TUBES	41
BATTERY BANK	42

LED6000S
WIRED HEAD ONLY

110V / 16A - E705626

- LUMENS**
5000
- POWER**
42W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
108 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



SAMSUNG

- BUILT TO SURVIVE**
- > Robust ABS body absorbs knocks on site
 - > Drop tested to 2.5M
 - > Strong silicone sleeve protects light from damage
 - > Diffused polycarbonate lens offers glare reduction
 - > Tougher than previous model
 - > Less shadows
 - > More efficient - low power

- DESIGN**
- > British engineered design
 - > Friction grip head tilt function

- LIGHTWEIGHT**
- > Only 2.1 Kg
 - > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

- MULTI-FUNCTIONAL USE**
- > Sold as head only with universal fixing bracket

NEW AND IMPROVED FOR 2017

The LED6000S: A high performance, lightweight, low power floodlight. Ideal for industrial environments.



EFFICIENT HEAT SINK
HEAT EXCHANGER TRANSFERS HEAT EFFICIENTLY TO ENSURE LIFE SPAN OF LEDS

TOUGH
SILICONE SLEEVE PROTECTS LIGHT FROM DAMAGE

SHATTERPROOF
FROSTED POLYCARBONATE LENS DIFFUSES THE LIGHT AND REDUCES SHADOWS



ROBUST
STRONG ABS BODY ABSORBS KNOCKS

SMART
UPGRADED LED DRIVER FOR GREAT EFFICIENCY

HIGH PERFORMANCE
108 SAMSUNG LEDS GENERATE 5000 LUMENS OF CRISP BRIGHT LIGHT

MULTI USE
UNIVERSAL FIXING BRACKET - SHOULDER STRAP INCREASES STRENGTH

LED6000S SINGLE WITH SCAFFOLD FIXING

110V / 16A - E705636

- LUMENS**
5000
- POWER**
42W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
108 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Light head affixed to a secure scaffold gripper
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED6000S SINGLE WITH MAGNETIC FIXING

110V / 16A - E705635

- LUMENS**
5000
- POWER**
42W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
108 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Base with two industrial magnets
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED6000S SINGLE WITH FIXED LEG TRIPOD

110V / 16A - E705633

- LUMENS**
5000
- POWER**
42W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
108 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Robust steel powder coated tripod
- > Tripod adjustable from 1.5 - 2.5M
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED6000S TWIN WITH FIXED LEG TRIPOD

110V / 16A - E705664

- LUMENS**
10000
- POWER**
84W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
216 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Robust steel powder coated tripod
- > Tripod adjustable from 1.5 - 2.5M
- > Supplied with 5M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED6000S SINGLE WITH SWING LEG TRIPOD

110V / 16A - E705631

- LUMENS**
5000
- POWER**
42W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
108 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Robust steel tripod
- > Adjustable from 1.5 - 2.5M
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED6000S TWIN WITH SWING LEG TRIPOD

110V / 16A - E705665

- LUMENS**
10000
- POWER**
84W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
216 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Robust steel tripod
- > Adjustable from 1.5 - 2.5M
- > Supplied with 5M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED6000S TWIN WITH ALUMINIUM MAST

110V / 16A - E705630

- LUMENS**
10000
- POWER**
84W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
216 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Supplied with two LED6000S assembled ready for use
- > Lightweight mast, only 12Kg
- > Mast extendable to 3.2M - Camlock with twist lock handles
- > Supplied with 5M VDE approved H07RNF rubber cable and BSEN60309 110V 16A plug

LED6000S QUAD WITH WINCH MAST

110V / 16A - E705632

- LUMENS**
20000
- POWER**
168W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
432 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Supplied with four LED6000S assembled ready for use
- > Heavy duty construction - weighs 26Kg
- > Mast extendable to 4.2M - Hand operated winch mechanism
- > Supplied with 14M VDE approved H07RNF rubber cable and BSEN60309 110V 16A plug

LED3000S
WIRED HEAD ONLY

110V / 16A - E705619

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)



- BUILT TO SURVIVE**
- > Robust ABS body absorbs knocks on site
 - > Drop tested to 1.5M
 - > Diffused polycarbonate lens offers glare reduction
 - > Tough
 - > Less shadows
 - > Low power

- DESIGN**
- > British engineered compact design
 - > Friction grip head tilt function

- LIGHTWEIGHT**
- > Only 2.1Kg
 - > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

- MULTI-FUNCTIONAL USE**
- > Sold as head only with universal fixing bracket

NEW AND IMPROVED FOR 2017

The LED3000S is a smart and lightweight floodlight.



EFFICIENT HEAT SINK

HEAT EXCHANGER TRANSFERS HEAT EFFICIENTLY TO ENSURE LIFE SPAN OF LEDs

SHATTERPROOF

FROSTED LENS DIFFUSES THE LIGHT



ROBUST
STRONG ABS BODY ABSORBS KNOCKS

SMART
UPGRADED LED DRIVER FOR GREAT EFFICIENCY

HIGH PERFORMANCE

65 LEDs GENERATE 3000 LUMENS OF CRISP BRIGHT LIGHT

MULTI USE
UNIVERSAL FIXING BRACKET - SHOULDER STRAP INCREASES STRENGTH

LED3000S SINGLE WITH SCAFFOLD FIXING

110V / 16A - E705637

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Light head affixed to a secure scaffold gripper
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED3000S SINGLE WITH MAGNETIC FIXING

110V / 16A - E705638

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Base with two industrial magnets
- > Supplied with 2M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED3000S SINGLE WITH FIXED LEG TRIPOD

110V / 16A - E705641

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Robust steel powder coated tripod
- > Tripod adjustable from 1.5 - 2.5M
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED3000S TWIN WITH FIXED LEG TRIPOD

110V / 16A - E705660

- LUMENS**
6000
- POWER**
60W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
130 LEDs
- COLOUR TEMP**
6500K (daylight white)




- > Robust steel powder coated tripod
- > Tripod adjustable from 1.5 - 2.5M
- > Supplied with 5M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED3000S SINGLE WITH SWING LEG TRIPOD

110V / 16A - E705661

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120°
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)




- > Robust steel tripod
- > Adjustable from 1.5 - 2.5M
- > Supplied with 3M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED3000S TWIN WITH SWING LEG TRIPOD

110V / 16A - E705662

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Robust steel tripod
- > Adjustable from 1.5 - 2.5M
- > Supplied with 5M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug

LED3000S TWIN WITH ALUMINIUM MAST

110V / 16A - E705639

- LUMENS**
3000
- POWER**
30W
- LIGHT SPREAD**
120° (per head)
- RATING**
IP44
- LAMP**
65 LEDs
- COLOUR TEMP**
6500K (daylight white)



- > Supplied with two LED3000S assembled ready for use
- > Lightweight mast, only 12Kg
- > Mast extendable to 3.2M - Camlock with twist lock handles
- > Supplied with 5M VDE approved H05RNF rubber cable and BSEN60309 110V 16A plug



DF1200
LED FLOODLIGHT

110V / 16A - E204000
240V / 13A - E204010

NEW

- LUMENS** 1200
- POWER** 20W
- LIGHT SPREAD** 120°
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)

> **IMPACT RESISTANT** - Pressure die cast aluminium case absorbs knocks with ease


> **ANTI-GLARE** - Frosted shatterproof lens defuses the light

> **ENERGY SAVING** - 95% more efficient than Halogen lights

> **COLOUR TEMP** - 6000K cool white light

> **CABLE & PLUG** - 5M H05RN-F rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

> **LIGHTWEIGHT** - 1.7Kg




NEW!
LED RANGE

The DF1200 is a comprehensive range of floodlights.

DF1200 SINGLE
WITH SCAFFOLD FIXING

110V / 16A - E705647
240V / 13A - E705654



- > Light head affixed to a secure scaffold gripper
- > Supplied with 5M H05RN-F rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 SINGLE
WITH MAGNETIC FIXING

110V / 16A - E705646
240V / 13A - E705653



- > Base with two industrial magnets
- > Supplied with 5M H05RN-F rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 SINGLE
WITH FLOOR BASE

110V / 16A - E204030
240V / 13A - E204020
BATTERY - E709286




- > Supplied with 2M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug (powered model)
- > Li-Ion rechargeable battery and cable for AC, DC car charger and USB cable
- > Delivers 2.5 hours operation. Charge time 5 hours (E709286 rechargeable model only)

DF1200 SINGLE
WITH FIXED LEG TRIPOD

110V / 16A - E705642
240V / 13A - E705648

- LUMENS** 1200
- POWER** 20W
- LIGHT SPREAD** 120°
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)



- > Supplied with two DF1200 light head
- > Robust steel powder coated tripod - height adjustable from 1.5 - 2.5M
- > Supplied with 5M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 TWIN
WITH FIXED LEG TRIPOD

110V / 16A - E705643
240V / 13A - E705649

- LUMENS** 2400
- POWER** 40W
- LIGHT SPREAD** 120° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)



- > Supplied with two DF1200 light head
- > Robust steel powder coated tripod - height adjustable from 1.5 - 2.5M
- > Supplied with 3M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 SINGLE
WITH TELESCOPIC TRIPOD

110V / 16A - E204050
240V / 13A - E204040

- LUMENS** 1200
- POWER** 20W
- LIGHT SPREAD** 120°
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)



- > Supplied with one DF1200 light head
- > Tripod height adjustable from 0.6-1.7M
- > Supplied with 3M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 TWIN
WITH TELESCOPIC TRIPOD

110V / 16A - E204070
240V / 13A - E204060

- LUMENS** 2400
- POWER** 40W
- LIGHT SPREAD** 120° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)



- > Supplied with two DF1200 light head
- > Tripod height adjustable from 0.6 - 1.7M
- > Supplied with 3M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 SINGLE
WITH SWING LEG TRIPOD

110V / 16A - E705644
240V / 13A - E705650

- LUMENS** 1200
- POWER** 20W
- LIGHT SPREAD** 120°
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)



- > Supplied with one DF1200 light head
- > Robust steel tripod
- > Tripod height adjustable from 1.5 - 2.5M
- > Supplied with 5M H05RN-F rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

DF1200 TWIN
WITH SWING LEG TRIPOD

110V / 16A - E705645
240V / 13A - E705651

- LUMENS** 2400
- POWER** 40W
- LIGHT SPREAD** 120° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** LED
- COLOUR TEMP** 6500K (daylight white)



- > Supplied with two DF1200 light head
- > Robust steel tripod
- > Tripod height adjustable from 1.5 - 2.5M
- > Supplied with 5M H07RN-F rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug



TUNGSTEN HALOGEN WIRED HEAD ONLY

110V / 16A - E58258
240V / 13A - E58059

- LUMENS** 4346
- POWER** 400W
- LIGHT SPREAD** 60°
- RATING** IP44 110V / IP20 240V
- LAMP** 400W Tube
- COLOUR TEMP** 4000K (warm white)



> 400W Halogen fitting and tube
> Head only available (E58052)

> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug



HALOGEN SINGLE HEAD WITH FIXED LEG TRIPOD

110V / 16A - E702510
240V / 13A - E702535

- LUMENS** 4346
- POWER** 400W
- LIGHT SPREAD** 60°
- RATING** IP44 110V / IP20 240V
- LAMP** 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Robust steel powder coated tripod
> Tripod height adjustable from 1.5 - 2.5M

> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN TWIN HEAD WITH FIXED LEG TRIPOD

110V / 16A - E702520
240V / 13A - E702545

- LUMENS** 8692
- POWER** 2 x 400W
- LIGHT SPREAD** 60° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** 2 x 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Robust steel powder coated tripod
> Tripod height adjustable from 1.5 - 2.5M

> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN HEAD WITH SCAFFOLD FIXING

110V / 16A - E709020
240V / 13A - E709021



> Light head affixed to a secure scaffold gripper
> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN HEAD WITH MAGNETIC FIXING

110V / 16A - E709010
240V / 13A - E709015



> Base with two industrial magnets
> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN HEAD WITH MINIPOD FLOOR BASE

110V / 16A - E709007
240V / 13A - E709009



> Light head affixed to one piece steel floor base
> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN HEAD WITH FLOOR BASE

110V / 16A - E709090
240V / 13A - E709060



> Light head affixed to a steel floor base
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN SINGLE HEAD WITH SWING LEG TRIPOD

110V / 16A - E701510
240V / 13A - E701530

- LUMENS** 4346
- POWER** 400W
- LIGHT SPREAD** 60°
- RATING** IP44 110V / IP20 240V
- LAMP** 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Light head features a tough oval design
> Robust steel tripod

> Tripod height adjustable from 1.5 - 2.5M
> Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN TWIN HEAD WITH SWING LEG TRIPOD

110V / 16A - E701512
240V / 13A - E701532

- LUMENS** 8692
- POWER** 2 x 400W
- LIGHT SPREAD** 60° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** 2 x 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Light head features a tough oval design
> Robust steel tripod

> Tripod height adjustable from 1.5 - 2.5M
> Supplied with 5M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN SINGLE HEAD WITH TELESCOPIC TRIPOD

110V / 16A - E709095
240V / 13A - E709070

- LUMENS** 4346
- POWER** 400W
- LIGHT SPREAD** 60°
- RATING** IP44 110V / IP20 240V
- LAMP** 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

> Tripod height adjustable from 0.6 - 1.7M
> Tripod features a 'quick lock and release' height adjustment

HALOGEN TWIN HEAD WITH TELESCOPIC TRIPOD

110V / 16A - E709100
240V / 13A - E709080

- LUMENS** 8692
- POWER** 2 x 400W
- LIGHT SPREAD** 60° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** 2 x 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

> Tripod height adjustable from 0.6 - 1.7M
> Tripod features a 'quick lock and release' height adjustment

HALOGEN TWIN HEAD WITH ALUMINIUM MAST

110V / 16A - E705667

- LUMENS** 8692
- POWER** 2 x 400W
- LIGHT SPREAD** 60° (per head)
- RATING** IP44 110V / IP20 240V
- LAMP** 2 x 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Lightweight mast, only 12Kg
> Mast extendable to 3.2M

> Mast - Camlock with twist lock handles
> Supplied with 5M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN QUAD HEAD WITH HEAVY DUTY MAST

110V / 16A - E711025

- LUMENS** 17384
- POWER** 4 x 400W
- LIGHT SPREAD** 60° (per head)
- RATING** IP44 110V
- LAMP** 4 x 400W Tube
- COLOUR TEMP** 4000K (warm white)



> Heavy duty folding tripod 3M in diameter
> Tripod extends to 5M

> Ground fixing points on each leg
> Supplied with 14M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug





LED LUMINATOR
FLOODLIGHT TOWER

110V / 16A - E712661

The LED Luminator Floodlight Tower has been upgraded with new technologies and features to support user needs on site.



- LUMENS**
30000
 - POWER**
374W
 - LIGHT SPREAD**
360°
 - RATING**
IP44 110V
 - LAMP**
6 x CREE CXA LEDs
 - COLOUR TEMP**
6500K (daylight white)
- CREE**

- LED HEAD**
 - > 6x CREE CXA LED chips deliver 30000 Lumens of crisp bright light
- TELESCOPIC MAST**
 - > Light head mast extends the unit up to 4M
- DURABLE**
 - > Robust rotomolded plastic body for site use
- LINKABLE**
 - > Safely link up to 4 units off a 3kVA transformer

- WIND RESISTANT**
 - > Three supportive screw 'n' lock outriggers help the unit withstand winds up to 65mph
- COMPACT**
 - > Smaller footprint than standard generator lights gets into hard to reach locations
- MANAGE LIGHT POLLUTION**
 - > 360° or 180° light option - ideal for residential areas
 - > 30000 Lumens on full power/ 15000 Lumens on half power

- TRANSPORT UTILISATION**
 - > Time and space saving- fit up to 4 LED Luminators in one transit van. 90Kg
- LOW POWER**
 - > ECO power mode offers valuable energy savings
 - > Low consumption - only 374W
- GENERATOR UTILISATION**
 - > A 4kVA generator will easily power up to 7 units


LIGHT CANNON
RECHARGEABLE FLOODLIGHT

RECHARGEABLE - E713100

Portable, rechargeable lighting solution with CREE® LED technology.

Ideal for lighting remote areas without a power source.

- LUMENS**
2000
 - POWER**
20W
 - LIGHT SPREAD**
120°
 - RATING**
IP44 110V
 - LAMP**
6 x CREE XTE LEDs
 - COLOUR TEMP**
6500K (daylight white)
- CREE**



- > **EXCEPTIONAL PERFORMANCE** - Offers 8 hours light on full power
- > **VERSATILE** - Use as an inspection light or floodlight
- > **LIGHTWEIGHT AND COMPACT** - Only 8.5Kg
- > **BRIGHT** - 8 CREE® LEDs deliver 2000 Lumens of super bright light
- > **MAXIMUM COVERAGE** - Offered by the 120° beam angle

- > **DURABLE DESIGN** - Handles the tough rigours of site use
- > **TELESCOPIC MAST** - Unit extends up to 2.1M. Packed height 88cm
- > **CASE** - Supplied with carry case and shoulder straps
- > **THREE FUNCTIONS OF LIGHT** - Full power - 2000 Lumens half power and pulse - 1000 Lumens

- > **CHARGE POINT** - Li-ion battery - charge time 12 hours. 240V main charger supplied
- > **LCD DISPLAY** - Indicates battery level / time left (hours, mins)
- > ***CREE** - Pioneering innovator of high power LEDs





LED ZONE LIGHT
LED FLOODLIGHT

110V / 16A - E712881
240V / 13A - E712880



LUMENS 3000 **LIGHT SPREAD** 120° **LAMP** LED
POWER 50W **RATING** IP44 110V / IP20 240V **COLOUR TEMP** 6500K

- > Low energy, directional light
- > Use as a floor light or affix to a tripod (sold separately E712882)
- > Rubber molded design
- > Two rear mounted sockets 110V 16A / 240V 13A
- > Supplied with 5M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

TELESCOPIC TRIPOD **TRIPOD - E712882**



- > Affix to LED Zone Light only
- > Tripod extendable from 0.6 - 1.7M

LED TASK LIGHT
WITH TELESCOPIC TRIPOD

110V / 16A - E712679
240V / 13A - E712678

LUMENS 900
POWER 12W
LIGHT SPREAD 120°
RATING IP44 110V / IP20 240V
LAMP 120 SMD LEDs
COLOUR TEMP 6500K (daylight white)



- > Light head adjustable to 180°
- > Folding adjustable tripod supplied with cable wrap and cable tidy
- > Tripod extendable to 2.25M
- > Lightweight only 3.75Kg
- > Supplied with 3M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug



UPLIGHT RANGE
OFFERS A BROAD SPECTRUM OF LIGHTING OPTIONS AND MULTIPLE BASES

The Uplight: Pioneer, award winner and best seller.

Developed in 2001, in answer to user frustrations with the fragile and limiting lighting offered from ant-corrosive 5ft lights. The Uplight range of robust lighting solutions offer a 120° light spread and multiple display applications to extend its use.

- Now in its third generation, regular user feedback continues to influence and improve the Uplight design.
- > Durable and versatile across many applications
- > Low energy light stick - ideal for plastering, event lighting and general construction
- > Extended use - stand, lay or suspend
- > Multiple stick and base options to suit user needs

- AWARD WINNING**
- > Winner of UK Design Week 'Best Industrial Product' awards for Uplight V2
 - > Winner of Hire Association Europe 'Best New Product' for Uplight V2

LED UPLIGHT
4FT LIGHT STICK WITH TRIPOD BASE

LUMENS 1600
POWER 20W
LIGHT SPREAD 120°
RATING IP44 110V / IP20 240V
LAMP LED Philips Tube
COLOUR TEMP 6500K (daylight white)



- 110V / 16A - E712673
240V / 13A - E712676
- > Power socket for linking multiple units together
 - > Low energy LED light stick and base ideal for plastering, event lighting and general construction
 - > N.B. Tripod cannot be removed
 - > Supplied with 3M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

LED UPLIGHT
4FT LIGHT STICK WITH WOBBLE BASE

LUMENS 1600
POWER 20W
LIGHT SPREAD 120°
RATING IP44 110V
LAMP LED Philips Tube
COLOUR TEMP 6500K (daylight white)



- 110V / 16A - E712670
- > Power socket for linking multiple units together
 - > Self righting up to 75°
 - > N.B. Base to be filled after purchase
 - > Supplied with 3M H07 RNF rubber cable and BSEN60309 110V 16A plug



FLUORESCENT UPLIGHT
4FT LIGHT STICK WITH TRIPOD BASE

LUMENS 2462
POWER 36W
LIGHT SPREAD* 180° / 360°
RATING IP44 110V / IP20 240V
LAMP Fluorescent T8 tube
COLOUR TEMP 6000K (cool white)



- 110V / 16A - E712600
240V / 13A - E712610
- > Low energy Philips tube
 - > N.B. Tripod cannot be removed
 - > Supplied with 3M H07 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
 - > * 360° light spread with reflector removed

FLUORESCENT UPLIGHT
4FT LIGHT STICK WITH SPLITTER BASE

LUMENS 2462
POWER 36W
LIGHT SPREAD* 180° / 360°
RATING IP44 110V
LAMP Fluorescent T8 tube
COLOUR TEMP 6000K (cool white)



- 110V / 16A - E712650
- > Low energy Philips tube with splitter base
 - > 110V 4 way power splitter base can be purchased independently (E712654)
 - > Supplied with 3M H07 RNF rubber cable and BSEN60309 110V 16A plug
 - > * 360° light spread with reflector removed

FLUORESCENT UPLIGHT
4 FT LIGHT STICK ONLY

LUMENS 2462
POWER 36W
LIGHT SPREAD* 180° / 360°
RATING IP44 110V
LAMP Fluorescent T8 tube
COLOUR TEMP 6000K (cool white)



- 110V / 16A - E712658
- > Low energy Philips tube
 - > Suspend from ceilings or scaffolding using two secure brackets (not included)
 - > Supplied with 3M H07 RNF rubber cable and BSEN60309 110V 16A plug
 - > * 360° light spread with reflector removed


DL4000
LED LINKABLE LIGHT

110V / 16A - E712685
RAIL MAST - E712685.1
RAIL MAST, BRACKET & LIGHT - E712704

The DL4000 is a bright anti-glare LED light. It has been designed to easily link up, to create a secure hanging floodlight chain for work sites, walkways or tunnels.



- LUMENS**
4000
- POWER**
42W
- LIGHT SPREAD**
120°
- RATING**
IP44 110V
- LAMP**
104 Samsung LEDs
- COLOUR TEMP**
6500K (daylight white)

SAMSUNG



KEY SPECIFICATION

- > 3MTR H07RNF input
- > 3MTR (external) output H07RNF
- > Diffused lens offers glare reduction
- > Supplied with coupler BSEN 60309 rated, 16A plug and cable tidy
- > Compact - overall size 780 x 180 x 80mm
- > Rigid impact resistant rubber end caps for additional durability



IT'S MULTI-FUNCTIONAL:

- > Linkable - connect multiple lights to form a festoon string
- > Affix the light to ceilings, scaffolding and masts

IT'S EFFICIENT AND COST EFFECTIVE TO RUN:
> A 4kVA power supply will power 50 DL4000s

IT'S DURABLE- BUILT TO PERFORM:

- > End caps are over moulded for added protection
- > Vented for ultimate heat control
- > Concave base allows the DL4000 to be attached to pillars and scaffolding with ease



LED ANTI-CORROSIVE RANGE
2FT AND 5FT LED TASK LIGHTS

The LED anti-corrosive range of bright, low power tasklights.

LED is associated with:

- > Being cost-effective, more efficient and durable on site
- > They eliminate the bulb issues faced with fluorescent task lights

In a recent survey with 150 tradespeople, Defender found:

- > **THEY ARE POPULAR** - Over 60% likely to buy either 2ft/ 5ft anti-corrosives in the future
- > **LED TRANSFER** - Over 75% would be likely to switch to LED versions
- > **POWER TAKE OFF POINTS** - 68% use the power take off points

Source: Defender 2ft/ 5ft Task Light Research Feb- March 2017- Source 150 users.

LED ANTI-CORROSIVE STRING
2FT TASK LIGHT

- LUMENS**
1243
- POWER**
20W
- LIGHT SPREAD**
120°
- RATING**
IP44 110V
- LAMP**
SMD LEDs
- COLOUR TEMP**
6500K (daylight white)

NEW



E709280
2FT 20W LED ANTI-CORROSIVE
STRING TASK LIGHT 110V

- > Cable & plug - 5M cable each side with a BS1363 16A coupler and a BS1363 16A plug

E204055
2FT 20W LED ANTI-CORROSIVE STRING TASK
LIGHT WITH BATTERY BACK UP 110V

- > Features - a battery back up offering 3 hours lighting
- > Inlet - supplied with 3M H05RN-F rubber cable with 16A plug
- > Outlet - supplied with 3M H05RN-F rubber cable with 16A coupler
- > Supplied with hook brackets ideal for affixing the light to a roof

LED ANTI-CORROSIVE STRING
5FT TASK LIGHT

- LUMENS**
2510
- POWER**
40W
- LIGHT SPREAD**
120°
- RATING**
P44 110V / IP20 240V
- LAMP**
SMD LEDs
- COLOUR TEMP**
6500K (daylight white)

NEW



E709283
5FT 40W LED ANTI-CORROSIVE
STRING LIGHT 110V

- > Cable & plug - 4.75M cable with a BS1363 16A plug and 3.25M H05RN-F cable with a BS1363 16A coupler

E204065
5FT 40W LED ANTI-CORROSIVE STRING TASK
LIGHT WITH BATTERY BACK UP 240V

- > Features - a battery back up offering 3 hours lighting
- > Inlet - supplied with 4.75M H05RN-F rubber cable with 16A plug
- > Outlet - supplied with 3.25M H05RN-F rubber cable with 16A coupler
- > Supplied with hook brackets ideal for affixing the light to a roof

FLUORESCENT ANTI-CORROSIVE STRING
2FT 5FT STRING TASK LIGHT

The 2ft and 5ft fluorescent lights complete with hanging hooks create an alternative festoon style light that can be linked to other similar fixtures.

The hanging hooks allow the fitting to be suspended from fixtures on construction sites, in marquees or as a temporary lighting solution.

- LUMENS**
1136
- POWER**
36W
- LIGHT SPREAD**
180°
- RATING**
IP44 110V
- LAMP**
Fluorescent T8 tube
- COLOUR TEMP**
6000K (cool white)

- 1.
- 2.

1 - 2FT HEAD ONLY - E708615
> Cable and plugs: **see page 40**

2 - 2FT STRING - E708619.5
> Supplied with 3M in and out H05 VVF PVC cable and BSEN60309 110V 16A plug

- LUMENS**
2666
- POWER**
58W
- LIGHT SPREAD**
180°
- RATING**
IP44 110V
- LAMP**
Fluorescent T8 tube
- COLOUR TEMP**
6000K (cool white)

- 3.
- 4.

3 - 5FT HEAD ONLY - E58570
> Cable and plugs: **see page 40**

4 - 5FT STRING - E708700
> Supplied with 3M in and out H05 VVF PVC cable and BSEN60309 110V 16A plug



LED ANTI CORROSIVE RANGE
2FT AND 5FT LED TASK LIGHTS

NEW

The LED anti-corrosive range of bright low power task lights offer valuable energy savings and are cost efficient to run

In a recent survey with 150 tradespeople, Defender found:

- > **THEY ARE POPULAR** - Over 60% likely to buy either 2ft/ 5ft anti corrosives in the future
- > **LED TRANSFER** - Over 75% would be likely to switch to LED versions
- > **POWER TAKE OFF POINTS** - 68% use the power take off points

LED is associated with:

- > LED is cost-effective, more efficient and durable on site
- > They eliminate the bulb issues faced with fluorescent task lights


Source: Defender 2ft / 5ft Task Light Research Feb - March 2017

2FT LED ANTI-CORROSIVE
WITH FIXED LEG TRIPOD AND PTP

110V / 16A - E709282.1
240V / 13A - E709281.1

NEW

- LUMENS** 1243
- POWER** 20W
- LIGHT SPREAD** 120°
- RATING** IP44 110V / IP20 240V
- LAMP** SMD LEDs
- COLOUR TEMP** 6500K (daylight white)



- > 240V (only) cable & plug - 5M H05RN-F rubber cable each side with a BS1363 13A plug
- > Features - 2 x 13A 240V power take off points
- > 110V (only) cable & plug - 5M H05RN-F rubber cable each side with 16A plug
- > Features - 2 x 16A 110V power take off points

5FT LED ANTI-CORROSIVE
WITH FIXED LEG TRIPOD AND PTP

110V / 16A - E709285.1
240V / 13A - E709284.1

NEW

- LUMENS** 2510
- POWER** 40W
- LIGHT SPREAD** 120°
- RATING** IP44 110V / IP20 240V
- LAMP** SMD LEDs
- COLOUR TEMP** 6500K (daylight white)



- > 240V (only) cable & plug - 5M H05RN-F rubber cable each side with a BS1363 13A plug
- > Features - 2 x 13A 240V power take off points
- > 110V (only) cable & plug - 5M H05RN-F rubber cable each side with 16A plug
- > Features - 2 x 16A 110V power take off points




2FT FLUORESCENT ANTI-CORROSIVE
WITH FIXED LEG TRIPOD

A multi-use 2ft fluorescent light on a sturdy fixed leg tripod for use in confined areas.

The fixed leg tripod enables the light to stand safe and freely to face the desired direction.

The central fixing allows the light to work from a vertical position right through to a 'horizontal facing upwards' direction which is ideal for plastering and other ceiling work.

- LUMENS** 1136
- POWER** 36W
- LIGHT SPREAD** 180°
- RATING** IP44 110V
- LAMP** Fluorescent T8 tube
- COLOUR TEMP** 6000K (cool white)



- 2FT FIXED LEG - E708620**
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug
- 2FT FIXED LEG - E708625**
> With PTP
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug
- 2FT FIXED LEG - E708674**
> With PTP and battery backup
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug
- 2FT FOLD LEG - E709172**
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug

5FT FLUORESCENT ANTI-CORROSIVE
WITH FIXED LEG TRIPOD

A multi-use 5ft fluorescent light on a sturdy fixed leg tripod for use in confined work site areas.

The fixed leg tripod enables the light to stand safe and freely to face the desired direction.

Centre fixing allows the light to work from a vertical position right through to a 'horizontal facing upwards' direction which is ideal for plastering and other ceiling work.

- LUMENS** 2666
- POWER** 58W
- LIGHT SPREAD** 180°
- RATING** IP44 110V
- LAMP** Fluorescent T8 tube
- COLOUR TEMP** 6000K (cool white)



- 5FT FIXED LEG - E708635**
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug
- 5FT FIXED LEG - E708645**
> With PTP
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug
- 5FT FIXED LEG - E708672**
> With PTP and battery backup
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug
- 5FT FOLD LEG - E709173**
> Supplied with 3M H05 VVF PVC cable and BSEN60309 110V 16A plug



DC4000
CONTRACTOR LIGHT

110V / 16A - E712686

The DC4000 is a LED floor light system that offers crisp, bright anti-glare light. Its compact size enables the light to be positioned in confined spaces. Additionally the light is linkable for floodlighting larger work spaces.

-  **LUMENS**
4000
 -  **POWER**
42W
 -  **LIGHT SPREAD**
120°
 -  **RATING**
IP44 110V
 -  **LAMP**
104 Samsung LEDs
 -  **COLOUR TEMP**
6500K (daylight white)
- SAMSUNG**

KEY SPECIFICATION

- > 4000 Lumens output
- > Uses 104 Samsung LEDs
- > 3MTR H07RNF input
- > 1MTR (External) output H07RNF
- > Diffused lens offers glare reduction
- > Supplied with a Defender coupler BSEN 60309 rated, 16A plug and cable tidy
- > Compact - overall size (with stand) 790 x 250 x 130mm
- > Power take off point



IT'S MULTI-FUNCTIONAL

> Linkable - connect multiple floor lights

IT'S EFFICIENT AND COST EFFECTIVE TO RUN

- > A 4kVA power supply will easily power 50 DC4000s
- > Low power consumption - 42W

IT'S DURABLE- BUILT TO PERFORM

- > Rigid impact resistant rubber end caps for additional durability
- > Vented for ultimate heat control
- > Sturdy steel tripod leg
- > Leg retention locking feature and cable management for easy handling



2FT LED CONTRACTOR
FLOOR LIGHT WITH PTP

110V / 16A - E709278
240V / 13A - E709279

NEW

-  **LUMENS**
1243
-  **POWER**
20W
-  **LIGHT SPREAD**
120°
-  **RATING**
IP44 110V / IP20 240V
-  **LAMP**
SMD LEDs
-  **COLOUR TEMP**
6500K (daylight white)



> 110V (only) cable & plug - 4.75M H05RN-F rubber cable each side with 16A plug

> Features - 2 x 16A 110V power take off points

> 240V (only) cable & plug - 4.75M H05RN-F rubber cable each side with a BS1363 13A plug

> Features - 2 x 13A 240V power take off points



> Crisp bright white light - DC4000 LED Contractor Light
Fewer lights required to illuminate the same space



> Dimmer light output from Defender Fluorescent 2ft Floor light with PTP E708670

2FT FLUORESCENT CONTRACTOR
FLOOR LIGHT WITH PTP

110V / 16A - E708670
240V / 13A - E708665

-  **LUMENS**
1136
-  **POWER**
26W
-  **LIGHT SPREAD**
100°
-  **RATING**
IP44 110V / IP20 240V
-  **LAMP**
2x 2ft 18W Fluorescent tubes
-  **COLOUR TEMP**
6000K (cool white)



> 110V (only) cable & plug - 4.75M H05 VVF rubber cable each side with 16A plug

> Features - 2 x 16A 110V power take off points

> 240V (only) cable & plug - 4.75M H05 VVF rubber cable each side with a BS1363 13A plug

> Features - 2 x 13A 240V power take off points



DF1200 FLOOR LIGHT
RECHARGEABLE AND POWERED OPTIONS

110V / 16A - E204030
240V / 13A - E204020
RECHARGEABLE - E709286

- LUMENS**
1200
- POWER**
20W
- LIGHT SPREAD**
120°
- RATING**
IP44 110V / IP20 240V
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



NEW

- > **FEATURES** - Li-Ion rechargeable battery and cable for AC, DC car charger and USB cable (E709286 version only)
Supplied with 2M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
- > **RECHARGEABLE** - Delivers 2.5 hours operation. Charge time 5 hours (E709286 version only)
- > **IMPACT RESISTANT** - Tough polycarbonate case absorbs knocks with ease
- > **ANTI GLARE** - Toughened frosted glass diffuser
- > **ROBUST** - Supplied with tough floor stand



FLUORESCENT FLOOR LIGHT
LIGHTWEIGHT FLOOR LIGHT

110V / 16A - E709156
240V / 13A - E709151

- LUMENS**
1010
- POWER**
38W
- LIGHT SPREAD**
140°
- RATING**
IP44 110V / IP20 240V
- LAMP**
Fluorescent 2D tube
- COLOUR TEMP**
6000K (cool white)



- > Integral carrying handle for easy portability
- > Tough plastic light enclosure and body to withstand knocks and drops
- > Supplied with 3M H05 VWF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
- > Replacement tube part number: E709050.1
See page 43

FLUORESCENT FLOOR LIGHT
WITH TOUGH ABS BODY

110V / 16A - E709155
240V / 13A - E709150

- LUMENS**
1010
- POWER**
38W
- LIGHT SPREAD**
140°
- RATING**
IP44 110V / IP20 240V
- LAMP**
Fluorescent 2D tube
- COLOUR TEMP**
6000K (cool white)



- > Anti-shock rubber base and comfort grip handle provides dependable protection and stability
- > Tough polycarbonate lens and ABS body withstands knocks and drops
- > Highly polished reflector for maximum light reflection
- > Supplied with 3M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
- > Replacement tube part number: E709050.1
See page 43



LED400 FLOOR LIGHT

240V 13A - E204045
RECHARGEABLE - E712883

- LUMENS**
400
- POWER**
10W
- LIGHT SPREAD**
120°
- RATING**
IP20 240V
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



NEW

- > **IT'S BRIGHT** - 400 Lumens output at 100% / 200 Lumens at 25%
- > **IMPACT RESISTANT** - Pressure die cast aluminium case absorbs knocks with ease
- > **POWERED VERSION** - Supplied with 2M H05 RNF rubber cable and BS1363 240V 13A plug
- > **ANTI-GLARE** - Toughened frosted glass diffuser
- > **RECHARGEABLE VERSION** - Delivers 3 hours operation on full power. Charge time 4 hours
- > **RECHARGEABLE VERSION** - Li-Ion rechargeable battery and cable for AC, DC, car charger and USB cable
- > **ROBUST** - Supplied with tough floor stand

LED FLOOR LIGHT
RECHARGEABLE AND WIRED OPTIONS

110V / 16A - E709162
240V / 13A - E709164
RECHARGEABLE - E709192

- LUMENS**
932
- POWER**
12.5W
- LIGHT SPREAD**
100°
- RATING**
IP44 110V / IP20 240V
- LAMP**
120 Solid State LEDs
- COLOUR TEMP**
6500K (daylight white)




- > **STRONG** - Anti-shock rubber base provides dependable protection and stability
- > **DURABLE** - Tough polycarbonate lens and ABS body withstand knocks and drops
Supplied with 2M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
- > **LOW HEAT** - for lighting awkward areas where space is tight
- > **CHARGE TIME** - 6hrs
- > **RECHARGEABLE** - Battery life offers 6 hours on half power / 3 hours on full power (E709192 version only)

HALOGEN FLOOR LIGHT
WITH STEEL FRAME

110V / 16A - E709090
240V / 13A - E709060

- LUMENS**
4346
- POWER**
400W
- LIGHT SPREAD**
60°
- RATING**
IP44 110V / IP20 240V
- LAMP**
400W Tube
- COLOUR TEMP**
4000K (warm white)



- > Supplied with a 400W Halogen fitting and tube
- > Steel powder coated frame
- > Supplied with 3M H05 VWF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

HALOGEN MINIPOD
WITH STEEL FRAME

110V / 16A - E709007
240V / 13A - E709009

- LUMENS**
4346
- POWER**
400W
- LIGHT SPREAD**
60°
- RATING**
IP44 110V / IP20 240V
- LAMP**
400W Tube
- COLOUR TEMP**
4000K (warm white)



- > Supplied with a 400W Halogen fitting and tube
- > Robust steel powder coated frame tested to withstand harsh site conditions
- > Supplied with 3M H05 VWF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug

LED GRIP LAMP
INSPECTION LAMP

110V / 16A - E89795
240V / 13A - E89790

- LUMENS**
800
- POWER**
10W
- LIGHT SPREAD**
360°
- RATING**
IP20 240V
- LAMP**
LED ES bulb
- COLOUR TEMP**
6500K (daylight white)



- > Includes a 10W LED bulb (ES fitting)
- > Adjustable spring-loaded grip offers hands-free working
- > 800 Lumens crisp white light output
- > Supplied with 5M H05 RNF rubber cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
- > Tough mesh guards protect the lamp



GLS LAMP
INSPECTION LAMP

110V / 16A - E89774
240V / 13A - E89772



- LUMENS**
160
- POWER**
64W
- LIGHT SPREAD**
360°
- LAMP**
GLS bulb
- COLOUR TEMP**
4000K

- > Supplied with 5M H05 VVF PVC cable and BSEN60309 110V 16A plug or BS1363 240V 13A plug
- > Tough plastic mesh guard protects the lamp and users
- > Integrated hanging hook for hands-free working
- > Bulb not included

FLUORESCENT LAMP
INSPECTION LAMP

240V / 13A - E712816



- LUMENS**
523
- POWER**
20W
- LIGHT SPREAD**
180°
- LAMP**
Fluorescent ES tube
- COLOUR TEMP**
6000K

- > Supplied with 5M H05 VVF PVC cable and BS1363 240V 13A plug
- > Tough polycarbonate lens and polypropylene body provide robust impact protection
- > 2x floating hanging brackets offers multiple working positions
- > Low energy 20W lamp with high intensity reflector deliver high output glare-free light

LED HAND TORCH
RECHARGEABLE

E712809

- LUMENS**
64
- POWER**
1W
- LIGHT SPREAD**
60°
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



- > Rechargeable hand lamp ideal for inspection and servicing work
- > 26 solid state high output, low energy LEDs provide a wide bright light spread
- > Tough polycarbonate lens
- > Runtime: 3 hours full power, 6 hours half power

LED MINI MOBI
RECHARGEABLE & BATTERY OPTIONS

3 X AA BATTERIES - E712842
RECHARGEABLE - E712841

- LUMENS**
240
- POWER**
3W
- LIGHT SPREAD**
30°
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



- > Run time: up to 8 hours at 70%, up to 3 hours at 100%
- > Unit charged using a Micro B USB - 1M cable supplied
- > Shatter-proof frosted lens - protects from the risk of cuts
- > Charge time: 4 hours

10W LED HEAD TORCH
RECHARGEABLE

240V - E712924



- LUMENS**
400
- POWER**
10W
- LIGHT SPREAD**
15°
- LAMP**
LED
- COLOUR TEMP**
6500K

- > Aluminium head torch
- > Li-ion rechargeable battery
- > Ideal for on the spot inspection work
- > Runtime: 5 hours at 400 Lumens - 20 hours at 100 Lumens

5W LED HEAD TORCH
BATTERY 3 x AAA

E712923



- LUMENS**
200
- POWER**
5W
- LIGHT SPREAD**
15°
- LAMP**
LED
- COLOUR TEMP**
6500K

- > Ideal for on the spot inspection work
- > Three operating modes: Off, 50%, 100%
- > Runtime: 2 hours full power / 4 hours 50% power
- > Requires AAA batteries - (included)

LED 250 DUO TORCH
BATTERY 3 x AA

E712985

- LUMENS**
190 / 250
- POWER**
3 x AA
- LIGHT SPREAD**
15°
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



- > 2 in 1 flashlight / inspection lamp
- > Anodised aircraft grade aluminium body
- > Water and impact resistant
- > Powerful magnetic base
- > 3 x AA Batteries (included)

LED 400 TORCH
BATTERY 3 x AA

E712980

- LUMENS**
160 / 400
- POWER**
3 x AA
- LIGHT SPREAD**
15°
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



- > 2 in 1 flashlight / red emergency flasher
- > Anodised aircraft grade aluminium body
- > Water and impact resistant
- > Powerful magnetic base
- > 3 x AA Batteries (included)

LED TRANSPORT TORCH
RECHARGEABLE

E712990

- LUMENS**
125
- POWER**
12V Outlet
- LIGHT SPREAD**
15°
- LAMP**
LED
- COLOUR TEMP**
6500K (daylight white)



- > Anodised air-craft grade aluminium body
- > Durable impact - resistant construction
- > Rechargeable - fits into any 12V auto outlet
- > Battery runtime - 1 hour



LED FESTOON KIT
LED MODULES

22M 110V / 16A - E89332
22M 240V / 13A - E89331
50M 110V / 16A - E89333

- LUMENS**
1530
- POWER**
25W (22M) - 50W (50M)
- LIGHT SPREAD**
120°
- RATING**
IP44 (110V) / IP20 (240V)
- LAMP**
Solid state LEDs



- > Ultra low wattage consumption at 2.5W per module
- > Heat and glass free to remove the risk of cuts and burning
- > Injection moulded fittings and solid state lamp components take heavy knocks
- > Instant strike up provides full brightness
- > No lamp replacement
- > 2M spacing between light fittings
- > Ultra sonic sealing technology to give IP44 rating



22M ES LED FESTOON KIT
GLS STYLE BULB - 110V

110V / 16A - E89811

- LUMENS**
8000
- POWER**
100W
- LIGHT SPREAD**
240°
- RATING**
IP44
- LAMP**
LED Bulb (E56262)



- > Kit features hanging light chain with 10 holders, bulb fittings and guards
- > Fully insulated
- > 10 x 10W bulbs included

22M GLS FESTOON KIT
GLS BULB - 110V

22M ES 110V / 16A - E89810
22M BC 110V / 16A - E89820



- LUMENS**
5800
- POWER**
600W
- LIGHT SPREAD**
360°
- LAMP**
60W GLS

- > Kit features a hanging light chain with 10 holders, bulb fittings and guards
- > Robust plastic guards offer bulb protection
- > Fully insulated for indoor and outdoor use

100M GLS FESTOON STRING
GLS BULB - 110V



- > 100M Hanging light chain with ES or BC holders
- > Fully insulated for indoor and outdoor use
- > Bulbs and guards not included
- 110V - 33 ES HOLDERS AT 3M SPACING - E89320
- 110V - 33 BC HOLDERS AT 3M SPACING - E89330
- 110V - 20 ES HOLDERS AT 5M SPACING - E89325




22M ES 110V / 16A - E89810



GUARDS
x 10



ES BULBS
x 10



ES HOLDERS
x 10


22M BC 110V / 16A - E89820



GUARDS
x 10



BC BULBS
x 10



BC HOLDERS
x 10



LED ES BULBS
AVAILABLE IN PACKS OF 10

E56262



- > 10W LED bulb
- > 806 Lumens
- > Use with E89811 festoon kit

FESTOON GUARD
AVAILABLE AS SINGLES

E89852



- > Used to protect light bulbs in conjunction with festoon string lights
- > Use with: E89811 / E89320 / E89330 / E89325

HANGING HOOKS
AVAILABLE IN PACKS OF 10

E86330



- > Reduces trip hazards on site
- > Eliminates damage to power leads



1.5KVA TRANSFORMER

2 x 110V 16A 110V - E201512



- OUTLETS** 2 x 16A
- CABLE** 2M, 1.5mm, 3 Core H07 RNF
- STANDARD** BSEN 61558-1
- > Resettable circuit breaker
- > Supplied with 2M cable and 13A plug
- > Continuous rating 750W

2.25KVA TRANSFORMER

2 x 110V 16A 110V - E202212



- OUTLETS** 2 x 16A
- CABLE** 2M, 1.5mm, 3 Core H07 RNF
- STANDARD** BSEN 61558-1
- > Resettable circuit breaker
- > Supplied with 2M cable and 13A plug
- > Continuous rating 750W

3KVA TRANSFORMER

2 x 110V 16A 110V - E203010



- OUTLETS** 2 x 16A
- CABLE** 2M, 1.5mm, 3 Core H07 RNF
- STANDARD** BSEN 61558-1
- > Resettable circuit breaker
- > Continuous rating 1500W
- > Ideal for use with power tools
- > Supplied with 2M cable and 13A plug

3.3KVA WALL MOUNTED

2 x 110V 16A TRANSFORMER 110V - E205068



- OUTLETS** 2 x 16A
- STANDARD** BSEN 61558-1
- > Fully powder coated to prevent corrosion
- > Continuous rating 1650W
- > Includes entry point to enable fixed installation

5KVA WALL MOUNTED

4 x 110V 16A TRANSFORMER 110V - E205069



- OUTLETS** 4 x 16A
- STANDARD** BSEN 61558-1
- > Continuous rating 2500W
- > Includes entry point to enable fixed installation

5KVA TRANSFORMER

4 x 16A 1 x 32A 110V - ZE210028



- OUTLETS** 4 x 16A 1 x 32A
- STANDARD** BSEN 61558-1
- RATING** IP23
- > Protected by MCBs (miniature circuit breakers)
- > Double wound with safety earth screen
- > Includes entry point to enable fixed installation
- > Continuous rating 2500W

3KVA POWER POD TRANSFORMER

2 x 110V 16A TRANSFORMER 110V - E205100



- OUTLETS** 2 x 16A
- CABLE** 2M, 1.5mm, 3 Core H07 RNF
- STANDARD** BSEN 61558-1
- > Resettable circuit breaker
- > Low heat output - runs cooler than conventional transformers
- > Stackable design for easy storage
- > Rubber feet absorb shocks and maximise air cooling
- > Strap stores the power cable away when not in use
- > Continuous rating 1500W
- > Weight: 18Kg



- Versus imported 3.3kVA transformers, the Power Pod transformer has:
 - > More Steel: over 1Kilo
 - > Better quality sand to dissipate heat
 - > High-grade tough Du Pont Nylon plastic casing: prevents rust, chips or cracks
 - > Recessed outlets prevent them from being sheared off in harsh environments
 - > Power-on indicators for each socket show when tools are powered up

3.3KVA TRANSFORMER

1 x 16A 1 x 32A 110V - E203022



- OUTLETS** 1 x 16A 1 x 32A
- CABLE** 2M, 1.5mm, 3 Core H07 RNF
- STANDARD** BSEN 61558-1
- > Resettable circuit breaker
- > Continuous rating 1500W
- > Ideal for use with power tools
- > Supplied with 2M cable and 13A plug

7.5KVA SLIMLINE TRANSFORMER

4 x 16A 2 x 32A, 2 x LIGHTING 110V - E205076



- OUTLETS** 4 x 16A 2 x 32A 2 x LIGHTING
- STANDARD** BSEN 61558-1
- RATING** IP44
- > Hard wire lighting circuits - safety feature stops lights being disconnected when in use
- > Protected with Schneider miniature circuit breakers
- > Includes entry point to enable fixed installation
- > Continuous rating 3750W

10KVA AIR COOL

4 x 16A 2 x 32A TRANSFORMER 110V - ZE210022



- OUTLETS** 4 x 16A 2 x 32A
- STANDARD** BSEN 61558-1
- RATING** IP23
- > Protected by MCBs (miniature circuit breakers)
- > Double wound with safety earth screen
- > Includes entry point to enable fixed installation
- > Continuous rating 5000W

10KVA 3 PHASE

4 x 16A 2 x 32A TRANSFORMER 110V - ZE210027



- OUTLETS** 4 x 16A 2 x 32A
- STANDARD** BSEN 61558-1
- RATING** IP23
- > Protected by MCBs (miniature circuit breakers)
- > Double wound with safety earth screen
- > Includes entry point to enable fixed installation
- > Continuous rating 5000W

5KVA TRANSFORMER

1 x 16A 1 x 32A 110V - E205042



- OUTLETS** 2 x 16A
- CABLE** 2M, 2.5mm, 3 Core H05 VVF VDE
- STANDARD** BSEN 61558-1
- > Resettable circuit breaker
- > Ideal for use with power tools
- > Continuous rating 2500W
- > No plug fitted

3.3KVA STEP-UP TRANSFORMER

2 x 16A 240V - E203030



- OUTLETS** 2 x 16A
- CABLE** 2M, 1.5mm, 3 Core H07 RNF
- STANDARD** BSEN 61558-1
- > For use with 240V heaters
- > Continuous rating 1650W

3KVA HEATER TRANSFORMER

1 x 16A 1 x 32A 110V - E205062



- OUTLETS** 1 x 16A 1 x 32A
- CABLE** 2M, 2.5mm, 3 Core H05 VVF VDE
- STANDARD** BSEN 61558-1
- > For use with 110V heaters
- > No plug fitted
- > Continuous rating 1500W

10KVA 3 PHASE MK2 TRANSFORMER 4 x 16A 2 x 32A, 2 x LIGHTING 110V - E205078

- OUTLETS** 4 x 16A 2 x 32A 2 x LIGHTING
- RATING** IP44
- STANDARD** BSEN 61558-1



- > Hard wire lighting circuits - safety feature stops lights being disconnected when in use
- > Protected with Schneider miniature circuit breakers
- > Includes entry point to enable fixed installation
- > Continuous rating 5000W
- > Fixed with handles and robust legs
- > Size 500 x 430 x 440mm
- > Weight 85Kg



SPIDER BALL
3-WAY 16A SPLITTER

110V / 16A - E13200
240V / 16A - E13210

OUTLETS
4 x 16A

CABLE
3M, 1.5mm, 3 Core
BS 6500

RATING
IP44

STANDARD
BSEN 5733



> Tested on site to perform

> Durable nylon / rubber casing delivers protection in use

> Recessed outlets prevent shearing in use

> Visible neon power on indicators and cable management system

> 3M cable with 16A fitted plug and cable tidy



P.I.R. SITE SAVER
POWER SPLITTER UNIT

110V / 16A - S10600

OUTLETS
6 x 16A

CABLE
3M, 2.5mm, 3 Core
H05 VVF VDE

STANDARD
BSEN 5733



> Energy saving site distribution tower

> Features a 360° P.I.R. sensor

> Weighted sturdy base

> Power turns off automatically only to the P.I.R. connected sockets when there is not activity within the immediate vicinity of the site saver

110V UPLIGHT
4-WAY 16A SPLITTER

110V / 16A - E712654

OUTLETS
4 x 16A

CABLE
3M, 1.5mm, 3 Core
H07 RNF VDE

RATING
IP44

STANDARD
BSEN 5733



> Injection molded sturdy base

> Built to withstand knocks on-site

> 16A Fitted plug

> Docking station for Uplight: E702658

SPIDER POD
3-WAY 16A SPLITTER


110V / 16A - E13220

OUTLETS
3 x 16A

CABLE
1.5mm, 3 Core
H07 RNF VDE

RATING
IP44

STANDARD
BSEN 5733



> High impact, lightweight nylon shell for use in tough applications

> Flexible, multi-directional outlets supply power to multiple tools

> Compact design allows for easy transportation and storage

> 16A Fitted plug

110V 2-WAY
32A SPLITTER

110V / 16A - E13111

OUTLETS
2 x 32A

CABLE
3M, 4mm, 3 Core
H05 RNF VDE

RATING
IP44

STANDARD
BSEN 5733



> Fiberglass case

> 16A Fitted plug

110V 4-WAY
POWER SPLITTER UNIT

110V / 16A - E13115

OUTLETS
4 x 16A

CABLE
3M, 2.5mm, 3 Core
H05 VVF VDE

RATING
IP44

STANDARD
BSEN 5733



> Steel cased

> Protected by 2 x 20A MCBs

> Fitted 110V 16A plug

> For site or event use

110V 6-WAY
POWER SPLITTER UNIT

110V / 16A - E13125

OUTLETS
4 x 16A / 2 x 32A

CABLE
3M, 4mm, 3 Core
H05 VVF VDE

RATING
IP44

STANDARD
BSEN 5733



> Steel cased

> Fitted MCB

> Fitted 110V 32A plug

> Protected by 2 x 20A MCBs

> For site or event use

110V CLASSIC
4-WAY 16A SPLITTER

110V / 16A - E13104

OUTLETS
4 x 16A

CABLE
3M, 2.5mm, 3 Core
H05 VVF VDE

RATING
IP44

STANDARD
BSEN 5733



> Steel cased

> 16A Fitted plug

> Solid reliable power splitter box

110V 4 WAY
16A / 32A SPLITTER

240V / 16A - E13108

OUTLETS
2 x 16A / 2 x 32A

CABLE
3M, 4mm, 3 Core
H05 VVF VDE

RATING
IP44

STANDARD
BSEN 5733



> Steel cased

> 32A Fitted plug

> Portable, tough reliable power distribution box

240V CLASSIC
4-WAY 16A SPLITTER

240V / 16A - E13112

OUTLETS
4 x 16A

CABLE
3M, 2.5mm, 3 Core
H05 VVF VDE

RATING
IP44


STANDARD
BSEN 5733



> Steel cased

> 16A Fitted plug

> Robust power splitter box



BATTERY BANK
CHARGING LOCKERS

240V / 16A - E92000

OUTLETS
10 x 2 Gang
240V 13A sockets

CABLE
3M, 1.5mm, 3 Core
H07-RNF VDE

RATING
IP44

STANDARD
BSEN 5733



> Coin return locking - compatible with current and new £1 coins

> 10 x 2 gang RCD protected 240V/ 13A outlets in each locker

> Fully earthed and protected by RCDs and an MCB

> 3M 1.5mm H07-RNF VDE rubber cable and BS1363 240V 16A plug

See page 42 for full specification

All Defender power splitters are hand made and undergo stringent electrical testing to give peace of mind

CABLE REEL RANGE FROM 5M - 50M

Defender cable reels come in varying lengths to support domestic and site requirements. All Defender cable reels are designed to give years of trouble free, safe use and include the following features:

- > **MOLDED PLUGS:** Non re-wireable plug for additional safety
- > **PLASTICS:** PP HDPE mix improved impact-resistant plastics pass advanced drop tests
- > **TESTED:** Independently UK tested by Bureau Veritas
- > **NEON INDICATOR:** See when it's switched on
- > **EASY WIND:** All reels are designed with a friction-free smooth coil action
- > **ANTI-TAMPER:** Anti-tamper screws and moulded inserts protect the face plate
- > **THERMAL CUT OUT:** Adds an extra layer of safety



5M, 10M, 15M CABLE REELS

5M, 1.25MM MINI CASSETTE 240V / 13A - E86560

- OUTLETS** 2 x 13A
- CABLE** 5M, 1.25mm, 3 Core H05-VVF BS 6500 VDE
- RATING** IP20
- STANDARD** BSEN 61242: 1998
- > Thermal cut out



10M, 1.25MM CASSETTE 240V / 13A - E86535

- OUTLETS** 4 x 13A
- CABLE** 10M, 1.25mm, 3 Core H05-VVF BS 6500 VDE
- RATING** IP20
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



15M, 1.5MM CASSETTE 110V / 16A - E86530

- OUTLETS** 2 x 16A
- CABLE** 15M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



15M, 1.5MM BOX REEL 240V / 13A - E86545

- OUTLETS** 4 x 13A
- CABLE** 15M, 1.25mm, 3 Core H05-VVF BS 6500 VDE
- RATING** IP20
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



20M CABLE REELS

1.5MM BOX REEL 110V / 16A - E86540

- OUTLETS** 2 x 16A
- CABLE** 20M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



REEL PRO 240V / 13A - E86355

- CABLE** 20M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP20
- > Start, stop lock out system
- > Use vertically and horizontally
- > Automatic anti-tangle cable reel dispenser



1.25MM LIGHT INDUSTRIAL 240V / 13A - E86465

- OUTLETS** 4 x 13A
- CABLE** 20M, 1.25mm, 3 Core H05-VVF BS 6500 VDE
- RATING** IP20
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



1.25MM LIGHT INDUSTRIAL 110V / 16A - E86470

- OUTLETS** 4 x 13A
- CABLE** 20M, 1.25mm, 3 Core H05-VVF BS 6500 VDE
- RATING** IP20
- STANDARD** BSEN 61242: 1998
- > Features a RCD Plug
- > Thermal cut out
- > Power indicator



25M CABLE REELS

1.5MM LIGHT INDUSTRIAL 240V / 16A - E86475

- OUTLETS** 2 x 16A
- CABLE** 25M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



1.5MM LIGHT INDUSTRIAL 110V / 16A - E86450

- OUTLETS** 2 x 16A
- CABLE** 25M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



2.5MM LIGHT INDUSTRIAL 110V / 16A - E86455

- OUTLETS** 2 x 16A
- CABLE** 25M, 2.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



1.5MM HEAVY DUTY 110V / 16A - E86505

- OUTLETS** 2 x 16A
- CABLE** 25M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



50M CABLE REELS

1.5MM HEAVY DUTY 110V / 16A - E86500

- OUTLETS** 2 x 16A
- CABLE** 50M, 1.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator




2.5MM HEAVY DUTY 110V / 16A - E86510

- OUTLETS** 2 x 16A
- CABLE** 50M, 2.5mm, 3 Core H05-VVF VDE
- RATING** IP44
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



1.5MM HEAVY DUTY 240V / 13A - E86515

- OUTLETS** 4 x 13A
- CABLE** 50M, 1.25mm, 3 Core H05-VVF BS 6500 VDE
- RATING** IP20
- STANDARD** BSEN 61242: 1998
- > Thermal cut out
- > Power indicator



Longer cable required? See page 36 for extension leads and fly leads

Build your own leads See page 38 for cable drums, plugs and sockets

EXTENSION LEADS RANGE
FROM 10M - 25M

Defender extension leads are fully certified - designed and manufactured to perform in harsh conditions.

The range of Defender fly leads are ideal for converting power to products with varying electrical current levels.

	10M 1.5MM CABLE CABLE H05-VVF VDE Low temperature Arctic	10M 2.5MM CABLE CABLE H05-VVF VDE Low temperature Arctic	14M 1.5MM CABLE CABLE H05-VVF VDE Low temperature Arctic	14M 2.5MM CABLE CABLE H05-VVF VDE Low temperature Arctic	14M 4.0MM CABLE CABLE H05-VVF VDE Low temperature Arctic	25M 1.5MM CABLE CABLE H05-VVF VDE Low temperature Arctic	25M 2.5MM CABLE CABLE H05-VVF VDE Low temperature Arctic	25M 4.0MM CABLE CABLE H05-VVF VDE Low temperature Arctic
240V / 13A 10 - 14M RATING IP20 BS EN 60309 plug and socket		•			•	•	•	•
110V / 16A 10 - 25M RATING IP44 BS EN 60309 plug and socket					•			•
240V / 16A 10 - 25M RATING IP20 BS EN 60309 plug and socket					•			•
110V / 32A 14 - 25M RATING IP20 BS EN 60309 plug and socket	•	•	•			•		
240V / 32A 14 - 25M RATING IP20 BS EN 60309 plug and socket	•	•	•			•		•

*Fixed with 32A Socket and 32A Coupler, DO NOT EXCEED 20AMPS

240V / 16A / 13A
FLY LEAD

240V - E85300



- > 250mm of Arctic blue 1.5MM H05-VVF PVC VDE cable
- > 16A plug to 13A socket
- > Max rating 13A

240V / 16A / 2X 13A
FLY LEAD

240V - E85302



- > 250mm of Arctic blue 1.5MM H05-VVF PVC VDE cable
- > 16A plug to 2 x 13A socket
- > Max rating 13A

240V / 16A / 4X 13A
FLY LEAD

240V - E85315



- > 500mm of Arctic blue 1.5MM H05-VVF PVC VDE cable
- > 16A plug to 4 x 13A socket
- > Ideal for caravanning

240V / 13A / 16A
FLY LEAD

240V - E85301



- > 250mm of Arctic blue 1.5MM H05-VVF PVC VDE cable
- > 13A plug to 16A socket
- > Max rating 13A

IN-LINE RCD UNIT
FLY LEAD

240V - E11085C



- > 1M of 1.5MM H05-VVF PVC VDE cable
- > 13A plug
- > 16A socket

110V / 32A / 16A
FLY LEAD

110V - E85323



- > 300mm of 1.5MM H05-VVF PVC VDE cable
- > 32A plug to 16A socket




EXTENSION LEADS RANGE PLUGS

All Defender cables are manufactured to applicable standards either VDE or BS6500 - available in varying lengths and cores.

Defender offers a comprehensive range of 13A, 16A and 32A plugs, sockets and couplers - all tested and independently accredited to the applicable standards.

	1.0MM - 2 CORE CABLE	1.0MM - 3 CORE CABLE	1.5MM - 2 CORE CABLE		1.5MM - 3 CORE CABLE	2.5MM - 2 CORE CABLE	2.5MM - 3 CORE CABLE	4.0MM - 3 CORE CABLE
110V / 100M CABLE DRUMS  CABLE H05-VVF VDE Low temperature Arctic	.	.	 110V / 100M - E87050		 110V / 100M - E87115	 110V / 100M - E87060	 110V / 100M - E87125	 110V / 100M - E87235
240V / 100M CABLE DRUMS  CABLE H05-VVF VDE Low temperature Arctic	.	.	 240V / 100M - E87055		 240V / 100M - E87215	 240V / 100M - E87065	 240V / 100M - E87225	 240V / 100M - E87238
110V / 240V / 50M CABLE DRUMS  CABLE H07-RNF VDE Rubber cable	 110V / 240V / 50M - E87420	 110V / 240V / 50M - E87435	 110V / 240V / 50M - E87425		 110V / 240V / 50M - E87440	 110V / 240V / 50M - E87430	 110V / 240V / 50M - E87448	 110V / 240V / 50M - E87445

	13A / 240V ✓ 13A - BS 1363A	16A / 240V ✓ 16A - BS EN 60309	16A / 110V ✓ 16A - BS EN 60309		32A / 240V ✓ 32A - BS EN 60309	32A / 110V ✓ 32A - BS EN 60309
PLUGS	 PACK OF 10 - E882615	 1 BLISTER PACK - E884127 PACK OF 10 - E884130	 1 BLISTER PACK - E884002 PACK OF 10 - E884005		 1 BLISTER PACK - E884265 PACK OF 1 - E884260	 1 BLISTER PACK - E884255 PACK OF 10 - E884250
COUPLERS	.	 1 BLISTER PACK - E884177 PACK OF 10 - E884180	 1 BLISTER PACK - E884052 PACK OF 10 - E884055		 1 BLISTER PACK - E884285 PACK OF 1 - E884280	 1 BLISTER PACK - E884275 PACK OF 1 - E884270
PANEL SOCKETS	.	 1 BLISTER PACK - E884205 PACK OF 1 - E884200	 1 BLISTER PACK - E884105 PACK OF 1 - E884100		 1 BLISTER PACK - E884305 PACK OF 1 - E884300	 1 BLISTER PACK - E884295 PACK OF 1 - E884290
GANG SOCKETS	   1: 1 GANG PACK OF 10 - E882921 2: 2 GANG PACK OF 10 - E882923 3: 4 GANG PACK OF 10 - E882924



RCD PLUG
13A

240V / 13A - E11070C



- > 13A RCD plug
- > Rewireable
- > 40 MS tripping speed
- > 30MA
- > Test and reset function

RCD SOCKET
13A

240V / 13A - E11060C



- > 13A RCD plug and socket
- > No wiring - in line protection
- > 40 MS tripping speed
- > 30MA
- > Test and reset function

IN-LINE RCD UNIT
13A

240V / 13A - E11085C



- > 1M of 1.5MM H05-VVF PVC VDE cable
- > 13A plug
- > 16A socket
- > No wiring - in line protection
- > 40 MS tripping speed
- > 30MA
- > Test and reset function

RCD UNIT
13A-13A

240V - E11092



- > 2M of 1.5MM H05-VVF PVC VDE cable
- > 13A plug
- > 13A socket
- > Fibreglass case
- > 40 MS tripping speed
- > 30MA

RCD UNIT
13A-16A

240V - E11090



- > 2M of 1.5MM H05-VVF PVC VDE cable
- > 13A plug
- > 16A socket
- > Fibreglass case
- > 40 MS tripping speed
- > 30MA

PETROL GENERATORS
POWERED BY HONDA

2.7KVA-DP 2700X
1 x 110V 1 x 240V 16A

PETROL - G032700



- HONDA**
- > Honda GX 160 petrol engine
 - > Maintenance free NSm alternator
 - > Oil alert and overload protection
 - > 2.7kVA maximum
 - > 2.2kW continuous rating
 - > 34Kg
 - > 160CC

3.4KVA-DP 3400X
1 x 110V 1 x 240V 16A

PETROL - G033400



- HONDA**
- > Honda GX 200 petrol engine
 - > Maintenance free NSm alternator
 - > Oil alert and overload protection
 - > 3.4kVA maximum
 - > 2.7kW continuous rating
 - > 39Kg
 - > 200CC

5KVA-DP 5000X
2 x 110V 2 x 240V 16A

PETROL - G035000



- HONDA**
- > Honda GX 270 petrol engine
 - > Maintenance free NSm alternator
 - > Oil alert and overload protection
 - > 5kVA maximum
 - > 4.0kW continuous rating
 - > 64Kg
 - > 270CC

LED ES BULBS
AVAILABLE IN PACKS OF 10

E56262



- > 10W LED Bulb
- > 806 Lumens
- > Use with E89811 Festoon kit

60W GLS BULBS
110V / 240V

BC - E56161
ES - E56162



- > For use with GLS Festoon (E89810/ 898820), Gripper Lamp (E89785/E89780) & Inspection Lamp (E89774/E89772)
- > Light spread 360°
- > Box Qty: 100

2D FLUORESCENT
110V / 240V

E709050.1



- > 4 Pin
- > 38W
- > Colour Temp 6000K
- > 1010 Lumens
- > Light spread 140°

LED TUBE
2FT / 4FT / 5FT



- > For use with the LED Uplight
- 2FT - E705618 4FT - E712675 5FT - E705612

FLUORESCENT TUBES
2FT / 4FT / 5FT



- > For use with the Fluorescent Task Lights and Floor Lights
- 2FT 100V - 240V - E712079 5FT 100V - 240V - E56560
- > For use with Fluorescent Uplights
- 4FT 100V - 240V - E712078

C-CLASS HALOGENS
150W - 750W



- > For use with Halogen Floodlights and Task Lights and Floor Lights
- 150W 110V - E57012 400W 110V - E57058
- 150W 240V - E57103 400W 240V - E57059
- 230W 110V - E57055 750W 240V - E57105
- 230W 240V - E57057

FESTOON GUARD
AVAILABLE AS SINGLES

E89852



- > Used to protect light bulbs in conjunction with Festoon string lights
- > Use with: E89811 / E89320 / E89330 / E89325

HANGING HOOKS
AVAILABLE IN PACKS OF 10

E86330



- > Reduces trip hazards on site
- > Eliminates damage to power leads



BATTERY BANK


10 SECURE LOCKERS WITH CHARGE POINTS

Ideal for charging portable tool batteries and mobile phones.

At the end of the workday plug in, lock up and clock out. Return in the morning to fully charged tools.

KEY SPECIFICATION

- > Dimensions: Whole unit (h x w x d): 1877mm x 455mm x 275mm
- > Charging locker (h x w x d): 270mm x 200mm x 280mm
- > Management locker (h x w x d): 270mm x 420mm x 280mm
- > Outlets: 10 x 2 gang 240V 13A
- > Weight: 63Kg
- > Voltage: 240V
- > Mains cable: 3M 1.5mm H07-RNF VDE rubber cable and BS1363 240V 16A plug
- > Internal cable: 1.5mm H07-RNF VDE rubber cable



240V / 16A - E92000

A PATENTED LOCKER SYSTEM WITH:

- > 20 integral RCD protected power points and MCB protected inlet
- > Fully earthed and protected by RCDs and an MCB

FEATURES 10 SECURE LOCKERS, EACH WITH:

- > Coin return locking - compatible with current and new E1 coins
- > 2-gang RCD protected 13A outlets
- > Numbered keys for easy ID
- > Individual locker venting
- > Power on indicators
- > Each locker has 2 power points

INTEGRAL MANAGEMENT UNIT WITH:

- > MCB protected distribution unit
- > Hasp lock: padlock and 2 keys
- > Manager instructions and guide

SUPPORTING PRODUCTS:

- > 3.3kVA Step Up Transformer (E203030) - enables the Battery Bank to be powered from an 110V 16A supply - see page 30 for more information
- > 16A to 13A Fly Lead (E85301) - allows the Battery Bank to be used from a standard 240V 13A supply - see page 37 for more information

VDE WHAT DOES VDE MEAN?

To ensure that cables and hand tools such as screwdrivers are safe to use when working with electricity, standards are set for testing them - known as VDE.

VDE takes its acronym from the company Verband der Elektrotechnik (Originally - Association of German Electrical Engineers, now - Association for Electrical, Electronic & Information Technologies) in Germany who are responsible for testing and certifying tools and appliances.

The VDE standard is being recognised more and more these days especially in the light of health and safety regulations which are now everywhere in the building trade.

Seeing the VDE trademark on cable or hand tools such as pliers or screwdrivers gives assurance that it is safe to use. Alongside the VDE mark is often found a voltage limit which indicates the voltage that this tool is safe to work with. Like most safety standards, the voltage these tools are tested to is far and above the limit printed on the tool ensuring maximum safety.

To bear the VDE Certification Mark, tools are put through very rigorous testing to ensure that the quality, construction, safety and even ergonomics meet with protective requirements of the applicable EC Directive.

Defender cables undergo rigorous VDE testing to ensure maximum safety and peace of mind.

LIGHT SPREAD

To help you find the right lighting solution, a light spread is provided for each product. To obtain the data, each product undertakes an assessment of the light intensity and beam width. The test is conducted by renowned independent test house Lux TSI under strict laboratory conditions.




LUMENS

Total light output emitted by a light source eg a tube, lamp or reflector. The higher the figure, the brighter the light will be.


COLOUR TEMPERATURE (KELVIN SCALE)

Colour temperature is a way to describe the light appearance provided by a light bulb (lamp). It is measured in degrees of Kelvin (K) on a scale from 1,000 to 10,000.

Typically, commercial and residential lighting application Kelvin temperatures fall somewhere on a scale from 2000K to 6500K.



Its value determines whether light bulbs produce warm or cold light. Bulbs with a low Kelvin value produce a warm yellow light, while those with a higher Kelvin value produce a cool blue, more energising light. As a guide, the colour temperature of candlelight is about 2000K, Fluorescent and LED lights are between 2700 and 6500K, Halogen around 2800K.



Page	Section	Part Number	Description	Power	Amp
LIGHTING 110V / 16A					
6	FLOODLIGHTS	E705636	LED6000S Single with Scaffold Fixing	110V	16A
6	FLOODLIGHTS	E705666	LED6000S Single with Swing Leg Tripod	110V	16A
6	FLOODLIGHTS	E705626	LED6000S Wired Head Only	110V	16A
7	FLOODLIGHTS	E705632	LED6000S Quad with Winch Mast	110V	16A
7	FLOODLIGHTS	E705663	LED6000S Single with Fixed Leg Tripod	110V	16A
7	FLOODLIGHTS	E705635	LED6000S Single with Magnetic Fixing	110V	16A
7	FLOODLIGHTS	E705634	LED6000S Twin with Aluminium Mast	110V	16A
7	FLOODLIGHTS	E705664	LED6000S Twin with Fixed Leg Tripod	110V	16A
7	FLOODLIGHTS	E705665	LED6000S Twin with Swing Leg Tripod	110V	16A
8	FLOODLIGHTS	E705637	LED3000S Single with Scaffold Fixing	110V	16A
8	FLOODLIGHTS	E705661	LED3000S Single with Swing Leg Tripod	110V	16A
8	FLOODLIGHTS	E705619	LED3000S Wired Head Only	110V	16A
9	FLOODLIGHTS	E705641	LED3000S Single with Fixed Leg Tripod	110V	16A
9	FLOODLIGHTS	E705638	LED3000S Single with Magnetic Fixing	110V	16A
9	FLOODLIGHTS	E705639	LED3000S Twin with Aluminium Mast	110V	16A
9	FLOODLIGHTS	E705660	LED3000S Twin with Fixed Leg Tripod	110V	16A
9	FLOODLIGHTS	E705662	LED3000S Twin with Swing Leg Tripod	110V	16A
10	FLOODLIGHTS	E705646	DF1200 Single with Magnetic Fixing	110V	16A
10	FLOODLIGHTS	E705647	DF1200 Single with Scaffold Fixing	110V	16A
10	FLOODLIGHTS	E204050	DF1200 Single with Telescopic Tripod	110V	16A
10	FLOODLIGHTS	E204070	DF1200 Twin with Telescopic Tripod	110V	16A
10	FLOODLIGHTS	E204000	DF1200 Wired Head Only	110V	16A
10	FLOOR LIGHTS	E204030	DF1200 Single with Floor Base	110V	16A
11	FLOODLIGHTS	E705642	DF1200 Single with Fixed Leg Tripod	110V	16A
11	FLOODLIGHTS	E705644	DF1200 Single with Swing Leg Tripod	110V	16A
11	FLOODLIGHTS	E705643	DF1200 Twin with Fixed Leg Tripod	110V	16A
11	FLOODLIGHTS	E705645	DF1200 Twin with Swing Leg Tripod	110V	16A
12	FLOODLIGHTS	E709095	Halogen Single Head with Telescopic Tripod	110V	16A
12	FLOODLIGHTS	E709020	Halogen Head with Scaffold Fixing	110V	16A
12	FLOODLIGHTS	E709100	Halogen Twin Head with Telescopic Tripod	110V	16A
12	FLOODLIGHTS	E58058	Tungsten Halogen Wired Head Only	110V	16A
12	FLOOR LIGHTS	E709090	Halogen Head with Floor Base	110V	16A
12	FLOOR LIGHTS	E709007	Halogen Head with Minipod Floor Base	110V	16A
13	FLOODLIGHTS	E702510	Halogen Single Head with Fixed Leg Tripod	110V	16A
13	FLOODLIGHTS	E712510	Halogen Single Head with Swing Leg Tripod	110V	16A
13	FLOODLIGHTS	E711025	Halogen Quad Head with Mast	110V	16A
13	FLOODLIGHTS	E705667	Halogen Twin Head with Aluminium Mast	110V	16A
13	FLOODLIGHTS	E702520	Halogen Twin Head with Fixed Leg Tripod	110V	16A
13	FLOODLIGHTS	E701512	Halogen Twin Head with Swing Leg Tripod	110V	16A
14	FLOODLIGHTS	E712661	LED Luminator Floodlight Tower	110V	16A
16	FLOODLIGHTS	E712881	LED Zone Light Floodlight Head Only	110V	16A
16	TASK LIGHTS	E712679	LED Task Light with Telescopic Tripod	110V	16A
17	UPLIGHT TASK LIGHTS	E712650	4Ft Fluorescent Uplight Light Stick with Splitter Base	110V	16A
17	UPLIGHT TASK LIGHTS	E712600	4Ft Fluorescent Uplight Light Stick with Tripod Base	110V	16A
17	UPLIGHT TASK LIGHTS	E712673	4Ft LED Uplight Light Stick with Tripod Base	110V	16A
17	UPLIGHT TASK LIGHTS	E712670	4Ft LED Uplight Light Stick with Wobble Base	110V	16A
17	UPLIGHT TASK LIGHTS	E712658	4Ft Uplight Light Stick Only	110V	16A
18	TASK LIGHTS	E712685	DL4000 LED Linkable Light	110V	16A
18	TASK LIGHTS	E712704	DL4000 Light + Rail Mast + Bracket	110V	16A
19	TASK LIGHTS	E708615	2Ft Fluorescent Anti Corrosive - Head Only	110V	16A
19	TASK LIGHTS	E708619.5	2Ft Fluorescent Anti Corrosive String Light	110V	16A
19	TASK LIGHTS	E709208	2Ft LED Anti Corrosive String	110V	16A
19	TASK LIGHTS	E204055	2Ft LED Anti Corrosive String with Battery Back Up	110V	16A
19	TASK LIGHTS	E708700	Fluorescent 5ft Anti-Corrosive - Head Only	110V	16A
19	TASK LIGHTS	E58570	Fluorescent 5ft Anti-Corrosive String Light	110V	16A
19	TASK LIGHTS	E709283	LED 5ft Anti-Corrosive String	110V	16A
19	TASK LIGHTS	E204065	LED 5ft Anti-Corrosive String with Battery Back Up	110V	16A
20	TASK LIGHTS	E708620	2Ft Fluorescent Anti-Corrosive with a Fixed Leg Tripod	110V	16A
20	TASK LIGHTS	E708674	2Ft Fluorescent Anti-Corrosive with a Fixed Leg Tripod and Battery Back Up	110V	16A

Page	Section	Part Number	Description	Power	Amp
LIGHTING 110V / 16A					
20	TASK LIGHTS	E708625	2Ft Fluorescent Anti-Corrosive with a Fixed Leg Tripod and Power Take Off Points	110V	16A
20	TASK LIGHTS	E709172	2Ft Fluorescent Anti-Corrosive with Folding Tripod	110V	16A
20	TASK LIGHTS	E709282.1	2Ft LED Anti-Corrosive with Fixed Leg Tripod	110V	16A
21	TASK LIGHTS	E708635	5Ft Fluorescent Anti-Corrosive with a Fixed Leg Tripod	110V	16A
21	TASK LIGHTS	E708672	5Ft Fluorescent Anti-Corrosive with a Fixed Leg Tripod and Battery Back Up	110V	16A
21	TASK LIGHTS	E708645	5Ft Fluorescent Anti-Corrosive with a Fixed Leg Tripod and Power Take Off Points	110V	16A
21	TASK LIGHTS	E709173	5Ft Fluorescent Anti-Corrosive with Folding Tripod	110V	16A
21	TASK LIGHTS	E709285.1	5Ft LED Anti-Corrosive with Fixed Leg Tripod	110V	16A
22	FLOOR LIGHTS	E712686	DC4000 LED Contractor Light	110V	16A
23	FLOOR LIGHTS	E708670	2ft Fluorescent Anti Corrosive Contractor Light with Power Take Off Points	110V	16A
23	FLOOR LIGHTS	E709278	2ft LED Anti Corrosive Contractor Light	110V	16A
24	FLOOR LIGHTS	E204030	DF1200 Single with Floor Base	110V	16A
24	FLOOR LIGHTS	E709162	LED Floor Light	110V	16A
25	FLOOR LIGHTS	E709090	Halogen Head with Floor Base	110V	16A
25	FLOOR LIGHTS	E709007	Halogen Head with Minipod Floor Base	110V	16A
25	FLOOR LIGHTS	E709156	Lightweight Fluorescent Floor Light	110V	16A
25	FLOOR LIGHTS	E709155	Tough Fluorescent Floor Light	110V	16A
26	HAND LAMPS	E89774	GLS Inspection Lamp - ES fitting	110V	16A
26	HAND LAMPS	E89795	LED Grip Lamp	110V	16A
28	FESTOON LIGHTING	E89325	100M GLS Festoon Hanging Light Chain With 20 Holders ES Fittings	110V	16A
28	FESTOON LIGHTING	E89330	100M GLS Festoon Hanging Light Chain With 33 Holders BC Fittings	110V	16A
28	FESTOON LIGHTING	E89320	100M GLS Festoon Hanging Light Chain With 33 Holders ES Fittings	110V	16A
28	FESTOON LIGHTING	E89811	22M ES LED Festoon Kit - ES Fittings	110V	16A
28	FESTOON LIGHTING	E89820	22M GLS Festoon Kit - BC Fittings	110V	16A
28	FESTOON LIGHTING	E89810	22M GLS Festoon Kit - ES Fittings	110V	16A
28	FESTOON LIGHTING	E89332	22M LED Festoon Kit 2.5W	110V	16A
28	FESTOON LIGHTING	E89333	50M LED Festoon Kit 2.5W	110V	16A
LIGHTING ACCESSORIES 110V					
16	ACCESSORIES	E712882	Tripod for LED Zone Light	Accessories	N/A
18	ACCESSORIES	E712685.1	Rail Mast & Bracket for DL4000 LED Linkable Light	Accessories	N/A
28	ACCESSORIES	E712550	Wobble Base - for use only with LED Uplight (E712670)	Accessories	N/A
28	ACCESSORIES	E86330	10 Pack - Hanging Hooks	Accessories	N/A
28	ACCESSORIES	E89852	Festoon Guard	Accessories	N/A
41	ACCESSORIES	E56262	10 Pack - 10W LED Bulbs	110V	N/A
41	ACCESSORIES	E705618	2 Ft LED Tube	110V	16A
41	ACCESSORIES	E712675	4 Ft LED Tube	110V	16A
41	ACCESSORIES	E705612	5 Ft LED Tube	110V	16A
41	ACCESSORIES	E709050.1	2D Fluorescent Tube	110V / 240V	13A / 16A
41	ACCESSORIES	E57012	150W C Class Halogen Tube	110V	16A
41	ACCESSORIES	E57055	230W C Class Halogen Tube	110V	16A
41	ACCESSORIES	E57058	400W C Class Halogen Tube	110V	16A
41	ACCESSORIES	E56161	60W GLS Bulb	110V	16A

Page	Section	Part Number	Description	Power	Amp
LIGHTING 240V / 13A					
10	FLOODLIGHTS	E705653	DF1200 Single with Magnetic Fixing	240V	13A
10	FLOODLIGHTS	E705654	DF1200 Single with Scaffold Fixing	240V	13A
10	FLOODLIGHTS	E204040	DF1200 Single with Telescopic Tripod	240V	13A
10	FLOODLIGHTS	E204060	DF1200 Twin with Telescopic Tripod	240V	13A
10	FLOODLIGHTS	E204010	DF1200 Wired Head Only	240V	13A
10	FLOOR LIGHTS	E204020	DF1200 Single with Floor Base	240V	13A
11	FLOODLIGHTS	E705648	DF1200 Single with Fixed Leg Tripod	240V	13A
11	FLOODLIGHTS	E705650	DF1200 Single with Swing Leg Tripod	240V	13A
11	FLOODLIGHTS	E705649	DF1200 Twin with Fixed Leg Tripod	240V	13A
11	FLOODLIGHTS	E705651	DF1200 Twin with Swing Leg Tripod	240V	13A
12	FLOODLIGHTS	E709070	Halogen Single Head with Telescopic Tripod	240V	13A
12	FLOODLIGHTS	E709021	Halogen Head with Scaffold Fixing	240V	13A
12	FLOODLIGHTS	E709080	Halogen Twin Head with Telescopic Tripod	240V	13A
12	FLOODLIGHTS	E58059	Tungsten Halogen Wired Head Only	240V	13A
12	FLOOR LIGHTS	E709060	Halogen Head with Floor Base	240V	13A
12	FLOOR LIGHTS	E709009	Halogen Head with Minipod Floor Base	240V	13A
13	FLOODLIGHTS	E702535	Halogen Single Head with Fixed Leg Tripod	240V	13A
13	FLOODLIGHTS	E701530	Halogen Single Head with Swing Leg Tripod	240V	13A
13	FLOODLIGHTS	E702545	Halogen Twin Head with Fixed Leg Tripod	240V	13A
13	FLOODLIGHTS	E701532	Halogen Twin Head with Swing Leg Tripod	240V	13A
16	FLOODLIGHTS	E712881	LED Zone Light Floodlight Head Only	240V	13A
16	TASK LIGHTS	E712678	LED Task Light with Telescopic Tripod	240V	13A
20	TASK LIGHTS	E709281.1	2Ft LED Anti-Corrosive with Fixed Leg Tripod	240V	13A
21	TASK LIGHTS	E709284.1	5Ft LED Anti-Corrosive with Fixed Leg Tripod	240V	13A
23	FLOORLIGHTS	E708665	2ft Fluorescent Anti-Corrosive Contractor Light with Power Take Off Points	240V	13A
23	FLOORLIGHTS	E709279	2ft LED Anti-Corrosive Contractor Light	240V	13A
24	FLOOR LIGHTS	E204020	DF1200 Single with Floor Base	240V	13A
24	FLOORLIGHTS	E709164	LED Floor Light	240V	13A
24	FLOORLIGHTS	E204045	LED400 Floor Light	240V	13A
25	FLOOR LIGHTS	E709060	Halogen Head with Floor Base	240V	13A
25	FLOOR LIGHTS	E709009	Halogen Head with Minipod Floor Base	240V	13A
25	FLOORLIGHTS	E709151	Lightweight Fluorescent Floor Light	240V	13A
25	FLOORLIGHTS	E709150	Tough Fluorescent Floor Light	240V	13A
26	HAND LAMPS	E712816	Fluorescent Hand Lamp	240V	13A
26	HAND LAMPS	E89772	GLS Inspection Lamp - ES fitting	240V	13A
26	HAND LAMPS	E89790	LED Grip Lamp	240V	13A
28	FESTOON LIGHTING	E89331	22M LED Festoon Kit 2.5W	240V	13A
LIGHTING ACCESSORIES 240V					
16	ACCESSORIES	E712882	Tripod for LED Zone Light	Accessories	N/A
42	ACCESSORIES	E709050.1	2D Fluorescent Tube	110V / 240V	13A / 16A
42	ACCESSORIES	E712079	2 Ft Fluorescent Tube	240V	13A
42	ACCESSORIES	E712675	4 Ft Fluorescent Tube	240V	13A
42	ACCESSORIES	E705612	5 Ft Fluorescent Tube	240V	13A
42	ACCESSORIES	E57103	150W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E57057	230W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E57059	400W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E57105	750W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E56162	60W GLS Bulb	240V	13A

Page	Section	Part Number	Description	Power	Amp
RECHARGEABLE LIGHTING					
16	ACCESSORIES	E712882	Tripod for LED Zone Light	Accessories	N/A
42	ACCESSORIES	E709050.1	2D Fluorescent Tube	110V / 240V	13A / 16A
42	ACCESSORIES	E712079	2 Ft Fluorescent Tube	240V	13A
42	ACCESSORIES	E712675	4 Ft Fluorescent Tube	240V	13A
42	ACCESSORIES	E705612	5 Ft Fluorescent Tube	240V	13A
42	ACCESSORIES	E57103	150W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E57057	230W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E57059	400W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E57105	750W C Class Halogen Tube	240V	13A
42	ACCESSORIES	E56162	60W GLS Bulb	240V	13A
RECHARGEABLE LIGHTING					
10	FLOOR LIGHTS	E709286	DF1200 Single with Floor Base	Rechargeable	N/A
15	FLOODLIGHTS	E713100	Light Cannon Portable Rechargeable LED Floodlight	Rechargeable	N/A
24	FLOORLIGHTS	E709192	LED Floor Light	Rechargeable	N/A
24	FLOORLIGHTS	E712883	LED400 Floor Light	Rechargeable	N/A
26	HAND LAMPS	E712809	LED Hand Torch / Lamp	Rechargeable	N/A
26	PORTABLE LIGHTS	E712841	Rechargeable LED Mini Mobi Inspection Light	Rechargeable	N/A
27	TORCHES & FLASHLIGHTS	E712924	10W LED Head Torch	Rechargeable	N/A
BATTERY OPERATED LIGHTING					
10	FLOOR LIGHTS	E709286	DF1200 Single with Floor Base	Rechargeable	N/A
15	FLOODLIGHTS	E713100	Light Cannon Portable Rechargeable LED Floodlight	Rechargeable	N/A
24	FLOORLIGHTS	E709192	LED Floor Light	Rechargeable	N/A
24	FLOOR LIGHTS	E712883	LED400 Floor Light	Rechargeable	N/A
26	HAND LAMPS	E712809	LED Hand Torch / Lamp	Rechargeable	N/A
26	PORTABLE LIGHTS	E712841	Rechargeable LED Mini Mobi Inspection Light	Rechargeable	N/A
27	TORCHES & FLASHLIGHTS	E712924	10W LED Head Torch	Rechargeable	N/A
BATTERY OPERATED LIGHTING					
26	PORTABLE LIGHTS	E712842	Battery Powered LED Mini Mobi Inspection Light	Battery	N/A
27	TORCHES & FLASHLIGHTS	E712923	5W LED Head Torch	Battery	N/A
27	TORCHES & FLASHLIGHTS	E712985	LED 250 Duo Torch	Battery	N/A
27	TORCHES & FLASHLIGHTS	E712980	LED 400 Torch	Battery	N/A
27	TORCHES & FLASHLIGHTS	E712990	LED Pocket Torch	Battery	N/A

Page	Section	Part Number	Description	Power	Amp
POWER DISTRIBUTION 110V 16A					
32	POWER SPLITTERS	E13200	3 Way Spider Ball Power Splitter	110V	16A
32	POWER SPLITTERS	E13104	Classic 4 Way Power Splitter Distribution Unit	110V	16A
32	POWER SPLITTERS	E712655	Fluorescent Uplight 4 Way Power Splitter Base	110V	16A
32	POWER SPLITTERS	E13220	Spider Pod Power Splitter	110V	16A
33	POWER SPLITTERS	E13115	4 Way Mains Circuit Breaker (MCB) Protected Distribution Unit	110V	16A
34	CABLE REELS	E86540	20M Box Reel - 16A 2 Way 1.5mm	110V	16A
34	CABLE REELS	E86500	50M Industrial Trade Cable Reel - 16A 2 Way 1.5mm	110V	16A
35	CABLE REELS	E86530	15M Cassette Reel - 16A 2 Way 1.5mm	110V	16A
35	CABLE REELS	E86505	25M Industrial Trade Cable Reel - 16A 2 Way 2.5mm	110V	16A
35	CABLE REELS	E86450	25M Light Industrial Cable Reel - 16A 2 Way 1.5mm	110V	16A
35	CABLE REELS	E86455	25M Light Industrial Cable Reel - 16A 2 Way 2.5mm	110V	16A
35	CABLE REELS	E86510	50M Industrial Trade Cable Reel - 16A 2 Way 2.5mm	110V	16A
36	EXTENSION LEADS	E85118	10M Extension Lead - 16A 1.5mm Cable - Yellow	110V	16A
36	EXTENSION LEADS	E85123	10M Extension Lead - 16A 2.5mm Cable - Yellow	110V	16A
36	EXTENSION LEADS	E85111	14M Extension Lead - 16A 1.5mm Cable - Yellow	110V	16A
36	EXTENSION LEADS	E85121	14M Extension Lead - 16A 2.5mm Cable - Yellow	110V	16A
37	EXTENSION LEADS	E85230	25M Extension Lead - 16A 1.5mm Cable - Yellow	110V	16A
37	EXTENSION LEADS	E85233	25M Extension Lead - 16A 2.5mm Cable - Yellow	110V	16A
38	CABLE DRUMS	E87050	100M Drum - 1.5mm 2 Core Yellow HO5 VV-F Cable	110V	16A
39	CABLE DRUMS	E87115	100M Drum - 1.5mm 3 Core Yellow HO5 VV-F Cable	110V	16A
39	CABLE DRUMS	E87060	100M Drum - 2.5mm 2 Core Yellow HO5 VV-F Cable	110V	20A
39	CABLE DRUMS	E87125	100M Drum - 2.5mm 3 Core Yellow HO5 VV-F Cable	110V	20A
39	CABLE DRUMS	E87235	100M Drum - 4.0mm 3 Core Yellow HO5 VV-F Cable	110V	32A
38	PLUGS, SOCKETS AND COUPLERS	E884052	16A Coupler - Yellow - Display Packed	110V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884055	16A Coupler - Yellow	110V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884105	16A Panel Socket - Yellow - Display Packed	110V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884100	16A Panel Socket - Yellow	110V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884002	16A Plug - Yellow - Display Packed	110V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884005	16A Plug - Yellow	110V	16A

POWER DISTRIBUTION 110V 20 - 32A

32	POWER SPLITTERS	E13111	2 Way Power Splitter Distribution Unit - 32A	110V	32A
32	POWER SPLITTERS	E13108	4 Way Power Splitter Distribution Unit - 16A / 32A	110V	2 x 16A 2 x 32A
33	POWER SPLITTERS	E13125	6 Way Mains Circuit Breaker (MCB) Protected Distribution Unit - 4x 16A & 2 x 32A	110V	4 x 16A 2 x 32A
33	POWER SPLITTERS	S10600	6 Way P.I.R Site Saver Distribution Unit - 6 x 16A	110V	6 x 16A
37	FLY LEADS	E85323	32-16A Fly Lead - 32A (Plug) 16A (Socket)	110V	32A to 16A
36	EXTENSION LEADS	E85235	14M Extension Lead - 32A 2.5mm Cable - Yellow	110V	20A
37	EXTENSION LEADS	E85249	25M Extension Lead - 32A 2.5mm Cable - Yellow	110V	20A
37	EXTENSION LEADS	E85240	14M Extension Lead - 32A 4mm Cable - Yellow	110V	32A
37	EXTENSION LEADS	E85262	25M Extension Lead - 32A 4mm Cable - Yellow	110V	32A

Page	Section	Part Number	Description	Power	Amp
POWER DISTRIBUTION 110V 32A					
39	PLUGS, SOCKETS AND COUPLERS	E884275	32A Coupler - Yellow - Display Packed	110V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884270	32A Coupler - Yellow	110V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884295	32A Panel Socket - Yellow - Display Packed	110V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884290	32A Panel Socket - Yellow	110V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884255	32A Plug - Yellow - Display Packed	110V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884250	32A Plug - Yellow	110V	32A
38	CABLE DRUMS	E87420	50M Drum - 1.0mm 2 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
38	CABLE DRUMS	E87435	50M Drum - 1.0mm 3 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
38	CABLE DRUMS	E87425	50M Drum - 1.5mm 2 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
39	CABLE DRUMS	E87440	50M Drum - 1.5mm 3 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
39	CABLE DRUMS	E87430	50M Drum - 2.5mm 2 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
39	CABLE DRUMS	E87445	50M Drum - 2.5mm 3 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
39	CABLE DRUMS	E87448	50M Drum - 4.0mm 3 Core Black Rubber HO7 RN-F Cable	110V / 240V	13A / 16A
30	TRANSFORMER	E201512	1.5kVA Transformer 2 x 16A Outlets	240V in / 110V out	16A
30	TRANSFORMER	E202212	2.25kVA Transformer 2 x 16A Outlets	240V in / 110V out	16A
30	TRANSFORMER	E205100	3kVA Power Pod Transformer 1 x 16A Outlet	240V in / 110V out	16A
30	TRANSFORMER	E203010	3kVA Transformer 2 x 16A Outlets	240V in / 110V out	16A
30	TRANSFORMER	E203022	3.3kVA Transformer 1 x 16A & 1x 32A Outlets	240V in / 110V out	1 x 16A & 1x 32A Outlets
30	TRANSFORMER	E205062	3.3kVA Heater Transformer 1 x 32A & 1 x 16A Outlets	240V in / 110V out	1 x 32A & 1 x 16A Outlets
30	TRANSFORMER	E205042	5kVA Transformer 2 x 16A & 1 x 32A Outlets	240V in / 110V out	2 x 16A & 1 x 32A Outlets
30	TRANSFORMER	E203030	3.3kVA Step-Up Transformer 2 x 16A Outlets	240V in / 110V out	2 x 16A Outlets
30	TRANSFORMER	E205068	5kVA Wall Mounted Transformer 2 x 16A Outlets	240V in / 110V out	2 x 16A Outlets
31	TRANSFORMER	ZE210028	5kVA Site Transformer 4 x 16A & 1 x 32A Outlets	240V in / 110V out	4 x 16A & 1x 32A Outlets
31	TRANSFORMER	ZE210027	10kVA 3 Phase Site Transformer 4 x 16A & 2 x 32A Outlets	240V in / 110V out	4 x 16A & 2 x 32A Outlets
31	TRANSFORMER	ZE210022	10kVA Air Cooled Site Transformer 4 x 16A & 2 x 32A Outlets	240V in / 110V out	4 x 16A & 2 x 32A Outlets
31	TRANSFORMER	E205078	10kVA 3 Phase Site Transformer Mk2 4 x 16A & 2 x 32A, 2 x Lighting Outlets	240V in / 110V out	4 x 16A & 2 x 32A, 2 x Lighting Outlets
31	TRANSFORMER	E205076	7.5kVA Site Transformer 4 x 16A & 2 x 32A, 2 x Lighting Outlets	240V in / 110V out	4 x 16A & 2 x 32A, 2 x Lighting Outlets
31	TRANSFORMER	E205069	5kVA Wall Mounted Transformer 4 x 16A Outlets	240V in / 110V out	4 x 16A Outlets
41	GENERATOR	G032700	Power Dp2700x Portable Generator	PETROL	1 x 16A 240V 1 x 16A 110V
41	GENERATOR	G033400	Power Dp3400x Portable Generator	PETROL	1 x 16A 1 x 16A
41	GENERATOR	G035000	Power Dp5000x Portable Generator	PETROL	1 x 16A 240V 1 x 32A 110V

Page	Section	Part Number	Description	Power	Amp
POWER DISTRIBUTION 240V 13A					
34	CABLE REELS	E86560	5M Mini Cassette Reel - 13A 2 Way 1.25mm	240V	13A
35	CABLE REELS	E86535	10M Cassette Reel - 13A 4 Way 1.25mm	240V	13A
35	CABLE REELS	E86545	15M Box Reel - 13A 4 Way 1.25mm	240V	13A
35	CABLE REELS	E86465	20M Light Industrial Cable Reel - 13A 4 Way 1.25mm	240V	13A
35	CABLE REELS	E86470	20M Light Industrial Cable Reel - 13A 4 Way 1.25mm C/W RCD	240V	13A
35	CABLE REELS	E86355	20M ReelPro Retractable Cable Reel 16A 1.25mm	240V	13A
34	CABLE REELS	E86475	25M Light Industrial Cable Reel - 13A 2 Way 1.5mm	240V	13A
35	CABLE REELS	E86515	50M Industrial Trade Cable Reel - 13A 4 Way 1.25mm	240V	13A
36	EXTENSION LEADS	E85223	10M Extension Lead - 13A 1.5mm Cable - Blue	240V	13A
36	EXTENSION LEADS	E85222	14M Extension Lead - 13A 1.5mm Cable - Blue	240V	13A
36	EXTENSION LEADS	E85224	14M Extension Lead - 13A 2.5mm Cable - Blue	240V	13A
36	EXTENSION LEADS	E85211	14M Extension Lead - 16A 1.5mm Cable - Blue	240V	13A
38	PLUGS, SOCKETS AND COUPLERS	E882921	13A 1 Gang Rubber Socket (Box Of 10)	240V	13A
38	PLUGS, SOCKETS AND COUPLERS	E882923	13A 2 Gang Rubber Socket (Box Of 10)	240V	13A
38	PLUGS, SOCKETS AND COUPLERS	E882924	13A 4 Gang Rubber Socket	240V	13A
38	PLUGS, SOCKETS AND COUPLERS	E882615	13A Rubberised Nylon Plug (Box Of 10)	240V	13A
37	FLY LEADS	E85301	13-16A Fly Lead - 13A (Plug) 16A (Socket)	240V	13A TO 16A Max 13A
37	RCDs	E11085C	In-Line RCD Unit - 13A Plug & 16A Socket	240V	13A
40	RCDs	E11090	13-16A RCD Unit - 13A Plug & 16A Socket	240V	13A
40	RCDs	E11060C	13A RCD Plug & Socket Adaptor	240V	13A
40	RCDs	E11070C	13A RCD Wireable Plug	240V	13A
40	RCDs	E11085C	In-Line RCD Unit - 13A Plug & 16A Socket	240V	13A
40	RCDs	E11092	13-13A RCD Unit - 13A Plug & 13A Socket	240V	13A TO 16A

POWER DISTRIBUTION 240V 16A

32	POWER SPLITTERS	E13210	3 Way Spider Ball Power Splitter	240V	16A
32	POWER SPLITTERS	E13112	Classic 4 Way Power Splitter Distribution Unit - 16A	240V	16A
36	EXTENSION LEADS	E85212	10M Extension Lead - 16A 1.5mm Cable - Blue	240V	16A
36	EXTENSION LEADS	E85220	10M Extension Lead - 16A 2.5mm Cable - Blue	240V	16A
36	EXTENSION LEADS	E85221	14M Extension Lead - 16A 2.5mm Cable - Blue	240V	16A
37	EXTENSION LEADS	E85236	25M Extension Lead - 16A 1.5mm Cable - Blue	240V	16A
37	EXTENSION LEADS	E85234	25M Extension Lead - 16A 2.5mm Cable - Blue	240V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884177	16A Coupler - Blue - Display Packed	240V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884180	16A Coupler - Blue	240V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884205	16A Panel Socket - Blue - Display Packed	240V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884200	16A Panel Socket - Blue	240V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884127	16A Plug - Blue - Display Packed	240V	16A
38	PLUGS, SOCKETS AND COUPLERS	E884130	16A Plug - Blue	240V	16A
38	CABLE DRUMS	E87055	100M Drum - 1.5mm 2 Core Blue HO5 VV-F Cable	240V	16A
39	CABLE DRUMS	E87215	100M Drum - 1.5mm 3 Core Blue HO5 VV-F Cable	240V	16A
36	FLY LEADS	E85315	16-4 x 13A Fly Lead - 16A (Plug) 4 x 13A (Sockets)	240V	16A TO 13A
36	FLY LEADS	E85300	16-13A Fly Lead - 16A (Plug) 13A (Socket)	240V	16A TO 13A Max 13A
36	FLY LEADS	E85302	16-2 x 13A Fly Lead - 16A (Plug) 2 x 13A (Socket)	240V	16A TO 13A Max 13A

Page	Section	Part Number	Description	Power	Amp
POWER DISTRIBUTION 240V 20A - 32A					
36	EXTENSION LEADS	E85237	14M Extension Lead - 20A 2.5mm Cable - Blue	240V	20A
37	EXTENSION LEADS	E85249.5	25M Extension Lead - 20A 2.5mm Cable - Blue	240V	20A
37	EXTENSION LEADS	E85243	14M Extension Lead - 32A 4mm Cable - Blue	240V	32A
39	CABLE DRUMS	E87065	100M Drum - 2.5mm 2 Core Blue HO5 VV-F Cable	240V	20A
39	CABLE DRUMS	E87225	100M Drum - 2.5mm 3 Core Blue HO5 VV-F Cable	240V	20A
39	CABLE DRUMS	E87238	100M Drum - 4.0mm 3 Core Blue HO5 VV-F Cable	240V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884285	32A Coupler - Blue - Display Packed	240V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884280	32A Coupler - Blue	240V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884305	32A Panel Socket - Blue - Display Packed	240V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884300	32A Panel Socket - Blue	240V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884265	32A Plug - Blue - Display Packed	240V	32A
39	PLUGS, SOCKETS AND COUPLERS	E884260	32A Plug - Blue	240V	32A
41	GENERATOR	G032700	Power Dp2700x Portable Generator	PETROL	1 x16A 240V 1 x 16A 110V
41	GENERATOR	G033400	Power Dp3400x Portable Generator	PETROL	1 x16A 240V 1 x 16A 110V
41	GENERATOR	G035000	Power Dp5000x Portable Generator	PETROL	1 x16A 240V 1 x 32A 110V

SITE CHARGING

42	SITE CHARGING	E92000	Battery Bank 10 Door Charging unit	240V	16A
----	---------------	--------	------------------------------------	------	-----





HEAD OFFICE

Birchwood Price Tools,
Birch Park, Park Lodge Road,
Giltbrook, Nottingham NG16 2AR

Sales: +44 (0) 115 938 9000
Email: sales@birchwoodpricetools.com
Website: www.birchwoodpricetools.com